




PRODUCT DATA 2023

UNILOCK®

Calculate

paver and
wall projects
FASTER!



Email
directly
to your
Unilock
Dealer



Try **SPEED-CALC™**
by **UNILOCK®**



TABLE OF CONTENTS - BOSTON

PAVERS

ADA Paver	04
Arcana™	05
Artline™ Smooth	06
Artline™ Umbriano®	07
Beacon Hill™ Flagstone	08-09
Beacon Hill™ Smooth	10
Bristol Valley®	11
Brussels Block®	12
Camelot®	13
Copthorne®	14
Courtstone®	15
Dura-Mat™	16
Eco-Line®	17
Eco-Optiloc™	18
Eco-Priora™	19
Eco-Promenade®	20
Eco-Stone™	21
Granito™	22
Hex Paver™	23
Hollandstone™	24
Holland Premier™	25
Il Campo®	26
Mattoni™	27
Natural Stone Sandstone	28-30
Natural Stone Limestone	31-32

Nordic Cobble™	33
Optiloc™	34
Porcelain	35
Promenade™ Plank Paver	36
Revela™	37
Richcliff®	38
Series™	39
Thornbury™ Smooth	40
Town Hall®	41
Transition™	42
Treo® Premier	43
Treo® Smooth	44
Tribeca Cobble™	45
Turfstone™	46
Umbriano®	47-48
Westport™	49

RETAINING WALLS

Brussels Dimensional System™	50
Concord Wall™	51
DuraHold®	52-53
DuraHold2®	54
Estate Wall™	55-59
Lineo™ Dimensional Stone	60-61
SienaStone™	62
SienaEdge™	63

U-Cara® Multi Face Wall System	64-67
U-Cara® Modular System	68
U-Cara® Rail System	69-71

COPING, STEPS, PILLAR CAPS

Architectural Coping	72
Fullnose Edger™	73
Ledgestone™	74-75
Universal Coping & Base	76

FIRE FEATURES

Sunset Firepit	77
RomanStack™ Firepit	78

ACCESSORIES

Natural Stone Cleaners	79
Natural Stone Sealers	79
Paver Cleaners	79
Paver Sealers	79
Adhesive	80
Sands	80-81
Edge Restraints	81
Large Equipment (Unilyft, Paver Saver)	82-83
Drivecel™	84

DESCRIPTION OF EDGE DETAILS



Zero-Edge



Chamfered Edge



Rounded Bevel



Micro Bevel

APPLICATION INDEX



PEDESTRIAN



LIGHT VEHICULAR



HEAVY-DUTY VEHICULAR



ROADWAYS-STREETS




PERMEABLE




ROOF DECK



BORDERS & ACCENTS



RETAINING WALLS UNDER 3'



STRUCTURAL WALL



POOL COPING



STEP TREADS



STEPS



PILLAR



FIRE FEATURE



WALL COPING



GARDEN WALL



OUTDOOR KITCHEN



WATER FEATURE



SEAT WALLS

ADA Paver Premier



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
 Surface Texture - Smooth
 Joint Spacing - 3 mm

TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

DRIVE FRIENDLY

Can handle vehicular loads

TECHNICAL INFORMATION

Conforms to ASTM C936
 Eligible for LEED v4.1 credits

ADA PAVER 12 X 12	
Bundle Type	SINGLE
Plant Produced	NEW YORK
Thickness (mm)	70 MM

SQFT PER	Bundle	93.04
	Layer	11.63
	Section	-
	Stone	0.97

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	1.02
	Section	-
	Layer	11.81
	Bundle	94.49

SAILOR LNFT PER	SqFt	1.02
	Section	-
	Layer	11.81
	Bundle	94.49

UNITS PER	SqFt	1.03
	Section	-
	Bundle	96.00

LBS PER	Layer	415
	Section	-
	Bundle	3,316

COLORS	Reflectance	Stock
Charcoal	SR n/a SRI n/a	SO
Red	SR n/a SRI n/a	SO



CHARCOAL



RED

Single Unit



STANDARD
 300 x 300 x 70mm
 11 7/8 x 11 7/8 x 2 3/4
 96 units/Bundle
 .97 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY.** All measurements are nominal. Contact Unilock for more information.



	12 X 24	18 X 24	24 X 24
Bundle Type	SINGLE	SINGLE	SINGLE
Plant Produced	CHICAGO	CHICAGO	CHICAGO
Thickness (mm)	50 MM	50 MM	50 MM

SQFT PER	Bundle	36.00	54.00	72.00
	Layer	4.00	6.00	8.00
	Section	-	-	-
	Stone	2.00	3.00	4.00

PER BUNDLE	Layers	9.00	9.00	9.00
	Sections	-	-	-

SOLDIER LNFT PER	SqFt	0.49	0.50	0.50
	Section	-	-	-
	Layer	1.98	2.97	3.98
	Bundle	17.78	26.75	35.79

SAILOR LNFT PER	SqFt	0.99	0.66	0.50
	Section	-	-	-
	Layer	3.98	3.98	3.98
	Bundle	35.79	35.79	35.79

UNITS PER	SqFt	0.50	0.33	0.25
	Section	-	-	-
	Bundle	18.00	18.00	18.00

LBS PER	Layer	96	144	192
	Section	-	-	-
	Bundle	864	1,296	1,728

COLORS	Reflectance	Stock	Stock	Stock
Avorio	SR .56 SRI 66	✓	✓	✓
Corvara	SR .30 SRI 34	✓	✓	✓
Modena	SR .46 SRI 53	✓	✓	✓
Vivanto	SR .18 SRI 16	✓	✓	✓

APPLICATIONS



APPEARANCE

Edge Detail - Micro
Surface Texture - Smooth
Joint Spacing - 0 mm

TECHNOLOGIES

ENDURACOLOR™
Refined surface and long-lasting color

EASYCLEAN™

Factory Sealed to provide integral stain resistance

TECHNICAL INFORMATION

Conforms to ASTM C 1782
Eligible for LEED v4.1 credits



AVORIO



CORVARA







MODENA



VIVANTO

LAYING PATTERNS



X & T Slab Spacers
Bagged Separately

Single Units	12 X 24	18 X 24	24 X 24
	301 x 606 x 50mm 11 ⁷ / ₈ x 23 ⁷ / ₈ x 2" 18 units/Bundle 2 Sq.Ft./Stone SPECIAL ORDER	453 x 606 x 50mm 17 ⁷ / ₈ x 23 ⁷ / ₈ x 2" 18 units/Bundle 3 Sq.Ft./Stone	606 x 606 x 50mm 23 ⁷ / ₈ x 23 ⁷ / ₈ x 2" 18 units/Bundle 4 Sq.Ft./Stone SPECIAL ORDER

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. Unilock offers adjustable and stackable pedestal systems; please contact your Territory Manager for pricing and availability. **Product is not intended for vehicular applications.** All measurements are nominal. Unilock recommends to install Arcana using T and X Slab spacers. Please contact your sales manager for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro
 Surface Texture - Smooth
 Joint Spacing - 3 mm


TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



FOSSIL



STEEL MOUNTAIN

7 Unit Random Bundle



UNIT A
 125 x 169 x 70mm
 4 7/8 x 6 3/4 x 2 3/4"
 32 units/Bundle
 .23 Sq.Ft./Stone



UNIT B
 125 x 262.5 x 70mm
 4 7/8 x 10 3/8 x 2 3/4"
 32 units/Bundle
 .35 Sq.Ft./Stone

7 Unit Random Bundle



UNIT C
 125 x 337.5 x 70mm
 4 7/8 x 13 3/8 x 2 3/4"
 32 units/Bundle
 .45 Sq.Ft./Stone



UNIT D
 125 x 450 x 70mm
 4 7/8 x 17 3/4 x 2 3/4"
 32 units/Bundle
 .61 Sq.Ft./Stone



UNIT E
 187.5 x 225 x 70mm
 7 1/2 x 8 7/8 x 2 3/4"
 32 units/Bundle
 .45 Sq.Ft./Stone



UNIT F
 187.5 x 337.5 x 70mm
 7 1/2 x 13 3/8 x 2 3/4"
 16 units/Bundle
 .58 Sq.Ft./Stone



UNIT G
 187.5 x 450 x 70mm
 7 1/2 x 17 3/4 x 2 3/4"
 16 units/Bundle
 .91 Sq.Ft./Stone

		SMOOTH FINISH
	Bundle Type	RANDOM
	Plant Produced	NEW YORK
	Thickness (mm)	70 MM

SQFT PER	Bundle	93.25
	Layer	11.66
	Section	-
	Stone	0.49

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	2.06
	Section	-
	Bundle	192.00

LBS PER	Layer	388
	Section	-
	Bundle	3,100

COLORS	Reflectance	Stock
Fossil	SR .22 SRI 21	✓
Steel Mountain	SR .30 SRI 32	✓

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro
 Surface Texture - Umbriano Mottled
 Joint Spacing - 3 mm

TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

EASYSOAK™

Factory Sealed to provide integral stain resistance


COLORFUSION™

Subtly mottled colored finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



FRENCH GREY



WINTER MARVEL

7 Unit Random Bundle



UNIT A
 125 x 169 x 70mm
 4 7/8 x 6 3/4 x 2 3/4"
 32 units/Bundle
 .23 Sq.Ft./Stone



UNIT B
 125 x 262.5 x 70mm
 4 7/8 x 10 3/8 x 2 3/4"
 32 units/Bundle
 .35 Sq.Ft./Stone

7 Unit Random Bundle



UNIT C
 125 x 337.5 x 70mm
 4 7/8 x 13 3/8 x 2 3/4"
 32 units/Bundle
 .45 Sq.Ft./Stone



UNIT D
 125 x 450 x 70mm
 4 7/8 x 17 3/4 x 2 3/4"
 32 units/Bundle
 .61 Sq.Ft./Stone



UNIT E
 187.5 x 225 x 70mm
 7 1/2 x 8 7/8 x 2 3/4"
 32 units/Bundle
 .45 Sq.Ft./Stone



UNIT F
 187.5 x 337.5 x 70mm
 7 1/2 x 13 3/8 x 2 3/4"
 16 units/Bundle
 .58 Sq.Ft./Stone



UNIT G
 187.5 x 450 x 70mm
 7 1/2 x 17 3/4 x 2 3/4"
 16 units/Bundle
 .91 Sq.Ft./Stone

		UMBRIANO FINISH
	Bundle Type	RANDOM
	Plant Produced	NEW YORK
	Thickness (mm)	70 MM

SQFT PER	Bundle	93.25
	Layer	11.66
	Section	-
	Stone	0.49

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	2.06
	Section	-
	Bundle	192.00

LBS PER	Layer	414
	Section	-
	Bundle	3,310

COLORS	Reflectance	Stock
French Grey	SR .35 SRI 38	✓
Winter Marvel	SR .18 SRI 17	✓

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information.

Beacon Hill™ Flagstone 60mm

ENDURACOLOR™



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
 Surface Texture - Textured
 Joint Spacing - 7 mm


TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



ALMOND GROVE



FOSSIL



NEW YORK BLEND



STEEL MOUNTAIN

	Bundle Type	RANDOM
	Plant Produced	UXBRIDGE
	Thickness (mm)	60 MM

SQFT PER	Bundle	116.57
	Layer	11.66
	Section	-
	Stone	1.46

PER BUNDLE	Layers	10.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	0.80
	Section	-
	Layer	9.35
	Bundle	93.50

UNITS PER	SqFt	0.69
	Section	-
	Bundle	80.00

LBS PER	Layer	328
	Section	-
	Bundle	3,279

COLORS	Reflectance	Stock
Almond Grove	SR .25 SRI 25	✓
Fossil	SR .22 SRI 21	✓
New York Blend	SR n/a SRI n/a	✓
Steel Mountain	SR .30 SRI 32	✓

3 Unit Random Bundle



LARGE RECTANGLE
 380 x 570 x 60mm
 15 x 22 1/2 x 2 3/8"
 20 Units/Bundle
 2.08 SqFt./Stone



SQUARE
 380 x 380 x 60mm
 15 x 15 x 2 3/8"
 30 units/Bundle
 1.39 Sq.Ft./Stone



SMALL RECTANGLE
 380 x 190 x 60mm
 15 x 7 1/2 x 2 3/8"
 30 units/Bundle
 .69 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information.

Beacon Hill™ Flagstone 80mm



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
 Surface Texture - Textured
 Joint Spacing - 7 mm


TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



ALMOND GROVE

FOSSIL

STEEL MOUNTAIN

Bundle Type	RANDOM
Plant Produced	UXBRIDGE
Thickness (mm)	80 MM

SQFT PER	Bundle	73.22
	Layer	10.46
	Section	-
	Stone	1.31

PER BUNDLE	Layers	7.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	0.85
	Section	-
	Layer	8.86
	Bundle	62.00

UNITS PER	SqFt	0.76
	Section	8.00
	Bundle	56.00

LBS PER	Layer	405
	Section	-
	Bundle	2,832

COLORS	Reflectance	Stock
Almond Grove	SR .22 SRI 21	SO
Fossil	SR n/a SRI n/a	SO
Steel Mountain	SR n/a SRI n/a	SO

3 Unit Random Bundle



LARGE RECTANGLE
 360 x 540 x 80mm
 14 1/4 x 21 1/4 x 3 1/8"
 14 Units/Bundle
 2.08 SqFt/Stone



SQUARE
 360 x 360 x 80mm
 14 1/4 x 14 1/4 x 3 1/8"
 21 units/Bundle
 1.39 Sq.Ft./Stone



SMALL RECTANGLE
 360 x 180 x 80mm
 14 1/4 x 7 x 3 1/8"
 21 units/Bundle
 .69 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information.



		XL	SMALL RECTANGLE	
Bundle Type	RANDOM	SINGLE	SINGLE	RANDOM
Plant Produced	UXBRIDGE	UXBRIDGE	UXBRIDGE	UXBRIDGE
Thickness (mm)	60 MM	60 MM	60MM	80MM

SQFT PER	Bundle	116.57	116.57	104.91	73.22
	Layer	11.66	11.66	11.66	10.46
	Section	-	-	-	-
	Stone	1.46	5.83	0.78	1.31

PER BUNDLE	Layers	10.00	10.00	9.00	7.00
	Sections	-	-	-	-

SOLDIER LNFT PER	SqFt	-	0.32	0.80	-
	Section	-	-	-	-
	Layer	-	3.74	9.35	-
	Bundle	-	37.40	84.15	-

SAILOR LNFT PER	SqFt	0.80	0.53	1.60	0.85
	Section	-	-	-	-
	Layer	9.35	6.23	18.70	8.86
	Bundle	93.50	62.30	168.31	62.01

UNITS PER	SqFt	0.69	0.17	1.29	0.76
	Section	-	-	-	-
	Bundle	80.00	20.00	135.00	56.00

LBS PER	Layer	336	320	336	383
	Section	-	-	-	-
	Bundle	3,360	3,199	3,024	2,681

COLORS	Reflectance	Stock	Stock	Stock	Stock
Almond Grove	SR .25 SRI 25	✓	✓	✓	✓
Charcoal	SR n/a SRI n/a			✓	
Fossil	SR .22 SRI 21	✓	✓	✓	✓
New York Blend	SR n/a SRI n/a	✓	✓	✓	
Opal	SR .24 SRI 24	SO	✓	✓	
Steel Mountain	SR .30 SRI 32	✓	✓	✓	✓

APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Smooth
Joint Spacing - 7 mm


TECHNOLOGIES

ENDURACOLOR™
Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERNS



ALMOND GROVE



CHARCOAL



FOSSIL



NEW YORK BLEND



OPAL



STEEL MOUNTAIN

3 Unit Random Bundle				XL Sold Separately		Sold Separately	
	LARGE RECTANGLE 380 x 570 x 60mm 15 x 22 1/2 x 2 3/8" 20 Units/Bundle 2.08 SqFt./Stone	SQUARE 380 x 380 x 60mm 15 x 15 x 2 3/8" 30 units/Bundle 1.39 Sq.Ft./Stone	SMALL RECTANGLE 380 x 190 x 60mm 15 x 7 1/2 x 2 3/8" 30 units/Bundle .69 Sq.Ft./Stone		XL UNIT 950 x 570 x 60mm 37 1/2 x 22 1/2 x 2 3/8" 20 units/Bundle 5.83 Sq.Ft./Stone		SMALL RECTANGLE 380 x 190 x 60mm 15 x 7 1/2 x 2 3/8" 135 units/Bundle .78 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information. Please contact Customer Service for Opal configurations.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
 Surface Texture - Textured
 Joint Spacing - 7 mm

TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

EASYCLEAN™

Factory Sealed to provide integral stain resistance


COMFORT STEP™

Ultra-smooth surface texture

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



	Bundle Type	RANDOM
	Plant Produced	UXBRIDGE
	Thickness (mm)	60 MM

SQFT PER	Bundle	116.57
	Layer	11.66
	Section	-
	Stone	-

PER BUNDLE	Layers	10.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	0.80
	Section	-
	Layer	9.35
	Bundle	93.50

UNITS PER	SqFt	-
	Section	-
	Bundle	-

LBS PER	Layer	296
	Section	-
	Bundle	2,957

COLORS	Reflectance	Stock
Fossil	SR .22 SRI 21	✓
Steel Mountain	SR .30 SRI 32	✓
Walnut	SR n/a SRI n/a	✓



FOSSIL



STEEL MOUNTAIN



WALNUT

3 Unit Random Bundle		LARGE RECTANGLE 380 x 570 x 60mm 15 x 22 1/2 x 2 3/8" 20 Units/Bundle 2.08 SqFt./Stone		SQUARE 380 x 380 x 60mm 15 x 15 x 2 3/8" 30 units/Bundle 1.39 Sq.Ft./Stone		SMALL RECTANGLE 380 x 190 x 60mm 15 x 7 1/2 x 2 3/8" 30 units/Bundle .69 Sq.Ft./Stone
----------------------	---	---	---	---	--	--

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. This product is not intended for vehicular applications. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
 Surface Texture - Smooth
 Joint Spacing - 2 mm

TECHNOLOGIES

CLASSIC
 Budget-friendly traditional product mix

ANTIQUED

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

	HALF	STANDARD	XL
Bundle Type	SINGLE	SINGLE	SINGLE
Plant Produced	UXBRIDGE	UXBRIDGE	UXBRIDGE
Thickness (mm)	70 MM	70 MM	70 MM

SQFT PER	Bundle	88.70	88.60	76.56
	Layer	-	-	-
	Section	12.67	12.66	25.52
	Stone	0.20	0.40	0.80

PER BUNDLE	Layers	-	-	-
	Sections	7.00	7.00	3.00

SOLDIER LNFT PER	SqFt	1.72	1.44	0.86
	Section	21.84	18.27	21.84
	Layer	-	-	-
	Bundle	152.86	127.87	65.51


SAILOR LNFT PER	SqFt	2.87	1.73	1.43
	Section	36.33	21.84	36.54
	Layer	-	-	-
	Bundle	254.28	152.86	109.61

UNITS PER	SqFt	5.05	2.53	1.25
	Section	64.00	32.00	32.00
	Bundle	448.00	224.00	96.00

LBS PER	Layer	-	-	-
	Section	398	455	843
	Bundle	2,789	3,187	2,528




COLORS	Reflectance	Stock	Stock	Stock
Almond Grove	SR n/a SRI n/a	✓	✓	✓
Limestone	SR .28 SRI 29	✓	✓	✓

LAYING PATTERNS



ALMOND GROVE

LIMESTONE

Single Units		HALF 104 x 173 x 70mm 4 x 6 7/8 x 2 3/4" 448 units/Bundle .20 Sq.Ft./Stone		STANDARD 173 x 208 x 70mm 6 7/8 x 8 1/4 x 2 3/4" 224 units/Bundle .40 Sq.Ft./Stone		XL 208 x 348 x 70mm 8 1/4 x 13 3/4 x 2 3/4" 96 units/Bundle .80 Sq.Ft./Stone
---------------------	---	---	---	---	--	---

Notes: **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfler
 Surface Texture - Smooth
 Joint Spacing - 3 mm

TECHNOLOGIES

CLASSIC

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

		SQUARE SMOOTH	RECTANGLE SMOOTH
Bundle Type		SINGLE	SINGLE
Plant Produced		UXBRIDGE	UXBRIDGE
Thickness (mm)		60 MM	60 MM

SQFT PER	Bundle	115.50	111.33
	Layer	-	-
	Section	16.50	22.27
	Stone	0.28	0.41

PER BUNDLE	Layers	-	-
	Sections	7.00	5.00

SOLDIER LNFT PER	SqFt	1.79	1.19
	Section	29.53	26.57
	Layer	-	-
	Bundle	206.69	132.87


SAILOR LNFT PER	SqFt	1.79	1.79
	Section	29.53	39.86
	Layer	-	-
	Bundle	206.69	199.31

UNITS PER	SqFt	3.64	2.43
	Section	60.00	54.00
	Bundle	420.00	270.00

LBS PER	Layer	-	-
	Section	464	630
	Bundle	3,247	3,150

Colors	Reflectance	Stock	Stock
Almond Grove	SR n/a SRI n/a	✓	✓
Granite	SR .26 SRI 27	✓	✓
Midnight Charcoal	SR n/a SRI n/a		✓

LAYING PATTERNS



ALMOND GROVE



GRANITE



MIDNIGHT CHARCOAL

Single Unit



SQUARE

159.8 x 159.8 x 60mm
 6 3/8 x 6 3/8 x 2 3/8"
 420 Units/Bundle
 .28 SqFt/Stone



RECTANGLE

160 x 240 x 60mm
 6 3/8 x 9 1/2 x 2 3/8"
 270 Units/Bundle
 .41 SqFt/Stone

Important: A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - n/a
 Surface Texture - Textured
 Joint Spacing - 3 mm

TECHNOLOGIES

ELEGANCE™

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

EASYSOAK™

Factory Sealed to provide integral stain resistance

REALA™

Cast from historical brick

ULTIMA™

Up to 4x stronger than poured-in-place concrete



TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

		Bundle Type	SINGLE
		Plant Produced	AYR
		Thickness (mm)	60 MM
SQFT PER	Bundle		89.20
	Layer		11.15
	Section		-
	Stone		0.15
PER BUNDLE	Layers		8.00
	Sections		-
SOLDIER LNFT PER	SqFt		1.43
	Section		-
	Layer		15.99
	Bundle		127.95
SAILOR LNFT PER	SqFt		4.41
	Section		-
	Layer		49.21
	Bundle		393.70
UNITS PER	SqFt		6.73
	Section		-
	Bundle		600.00
LBS PER	Layer		294
	Section		-
	Bundle		2,349

COLORS	Reflectance	Stock
Basalt	SR n/a SRI n/a	✓
Burgundy Red	SR n/a SRI n/a	✓
Burnt Clay	SR n/a SRI n/a	✓
Old Oak	SR n/a SRI n/a	✓

LAYING PATTERNS



BASALT



BURGUNDY RED



BURNT CLAY



OLD OAK

Single Unit

STANDARD
 65 x 200 x 60mm
 2 5/8 x 7 7/8 x 2 3/8"
 600 Units/Bundle
 .15 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
 Surface Texture - Textured
 Joint Spacing - 15 mm

TECHNOLOGIES

ELEGANCE™

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

EASYCLEAN™

Factory Sealed to provide integral stain resistance

REALA™

Cast from European cobblestones

ULTIMA™


Up to 4x stronger than poured-in-place concrete

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

Bundle Type		RANDOM	
Plant Produced		AYR	
Thickness (mm)		60 MM	
SQFT PER	Bundle	98.30	
	Layer	12.29	
	Section	-	
	Stone	-	
PER BUNDLE	Layers	8.00	
	Sections	-	
SOLDIER LNFT PER	SqFt	-	
	Section	-	
	Layer	-	
	Bundle	-	
SAILOR LNFT PER	SqFt	2.25	
	Section	-	
	Layer	27.69	
	Bundle	221.52	
UNITS PER	SqFt	3.91	
	Section	-	
	Bundle	384.00	
LBS PER	Layer	291	
	Section	-	
	Bundle	2,326	
COLORS		Reflectance	Stock
Basalt		SR n/a SRI n/a	✓


LAYING PATTERNS



BASALT

5 Unit Random Bundle	XL RECTANGLE	LARGE RECTANGLE	RECTANGLE	SMALL RECTANGLE	SQUARE
	215 x 130 x 60mm 8 3/8 x 5 1/8 x 2 3/8"	185 x 130 x 60mm 7 1/4 x 5 1/8 x 2 3/8"	165 x 130 x 60mm 6 1/2 x 5 1/8 x 2 3/8"	145 x 130 x 60mm 5 3/4 x 5 1/8 x 2 3/8"	130 x 130 x 60mm 5 1/8 x 5 1/8 x 2 3/8"
	128 Units/Bundle .30 SqFt/Stone	64 Units/Bundle .28 SqFt/Stone	64 Units/Bundle .23 SqFt/Stone	64 Units/Bundle .20 SqFt/Stone	64 Units/Bundle .18 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
 Surface Texture - Smooth
 Joint Spacing - n/a

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

CLASSIC

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits



NATURAL

Single Unit



STANDARD
 500 x 500 x 100mm
 19 3/4 x 19 3/4 x 3 7/8"
 28 units/Bundle
 2.80 Sq.Ft./Stone

	CLASSIC FINISH
Bundle Type	SINGLE
Plant Produced	GORMLEY
Thickness (mm)	100 MM

SQFT PER	Bundle	78.40
	Layer	11.20
	Section	-
	Stone	2.80

PER BUNDLE	Layers	7.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	0.36
	Section	-
	Bundle	28.00

LBS PER	Layer	320
	Section	-
	Bundle	2,240

COLORS	Reflectance	Stock
Natural	SR .30 SRI 32	SO

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces.** All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro
 Surface Texture - Smooth / Exposed / Brushed /
 Umbriano Mottled
 Joint Spacing - 6.25 mm
 Void - 5.80%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ENDURACOLOR™

Refined surface and long-lasting color

EASYSOAK™ (Umbriano)

Factory Sealed to provide integral stain resistance

COLOR FUSION™ (Umbriano)

Subtly mottled color finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

	MULTIPLE FINISHES	
	Bundle Type	RANDOM
	Plant Produced	NEW YORK
	Thickness (mm)	100 MM

SQFT PER	Bundle	66.20
	Layer	11.03
	Section	-
	Stone	0.34

PER BUNDLE	Layers	6.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	2.90
	Section	-
	Bundle	192.00









LBS PER	Layer	504
	Section	-
	Bundle	3,027

COLORS	Reflectance	Stock
Multiple Colors and Finishes	SR n/a SRI n/a	SO

Other finishes are available - please contact your Territory Manager for more details.

LAYING PATTERNS



8 Unit Random Bundle								
	UNIT A 357 x 84 x 100mm 14 x 3 3/16 x 3 7/8" 20 Units/Bundle .32 SqFt/Stone	UNIT B 317 x 84 x 100mm 12 1/2 x 3 3/16 x 3 7/8" 20 Units/Bundle .29 SqFt/Stone	UNIT C 277 x 84 x 100mm 12 x 3 3/16 x 3 7/8" 20 Units/Bundle .25 SqFt/Stone	UNIT D 237 x 84 x 100mm 9 3/8 x 3 3/16 x 3 7/8" 20 Units/Bundle .21 SqFt/Stone	UNIT E 357 x 114 x 100mm 14 x 4 1/2 x 3 7/8" 20 Units/Bundle .44 SqFt/Stone	UNIT F 317 x 114 x 100mm 12 1/2 x 4 1/2 x 3 7/8" 20 Units/Bundle .39 SqFt/Stone	UNIT G 277 x 84 x 100mm 11 x 4 1/2 x 3 7/8" 20 Units/Bundle .34 SqFt/Stone	UNIT H 237 x 84 x 100mm 9 3/8 x 4 1/2 x 3 7/8" 20 Units/Bundle .29 SqFt/Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces.** All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
 Surface Texture - Smooth
 Joint Spacing - 12mm
 Void - 7.3%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through


CLASSIC

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



		CLASSIC FINISH
	Bundle Type	SINGLE
	Plant Produced	UXBRIDGE
	Thickness (mm)	80 MM

SQFT PER	Bundle	63.56
	Layer	9.08
	Section	-
	Stone	0.50

PER BUNDLE	Layers	7.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	1.98
	Section	-
	Bundle	126.00

LBS PER	Layer	292
	Section	-
	Bundle	2,047

COLORS	Reflectance	Stock
Natural	SR .30 SRI 32	SO



NATURAL

Single Unit



STANDARD
 250 x 250 x 80mm
 9 7/8 x 9 7/8 x 3 1/8"
 126 Units/Bundle
 .50 SqFt/Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro
 Surface Texture - Smooth
 Joint Spacing - 7mm
 Void - 4.6 - 7.08%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

CLASSIC

Budget-friendly traditional product mix


ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



	5X10" SMOOTH CLASSIC
Bundle Type	SINGLE
Plant Produced	UXBRIDGE
Thickness (mm)	80 MM

SQFT PER	Bundle	75.95
	Layer	-
	Section	-
	Stone	0.31

PER BUNDLE	Layers	-
	Sections	-

SOLDIER LNFT PER	SqFt	1.27
	Section	-
	Layer	-
	Bundle	96.46

SAILOR LNFT PER	SqFt	2.54
	Section	-
	Layer	-
	Bundle	192.91


UNITS PER	SqFt	3.23
	Section	-
	Bundle	245.00

LBS PER	Layer	-
	Section	-
	Bundle	2,620

COLORS	Reflectance	Stock
Almond Grove	SR n/a SRI n/a	✓
Granite	SR .26 SRI 27	✓



ALMOND GROVE



GRANITE

Single Unit



RECTANGLE
 120 x 240 x 80mm
 4 ¾ x 9 ½ x 3 ⅛
 245 units/Bundle
 .31 Sq.Ft./Stone

Notes: **Available in other finishes. SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces.**
 All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro
 Surface Texture - Smooth & Series Exposed
 Joint Spacing - 7 mm
 Void - 10.12 %

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ENDURACOLOR™

Refined surface and long-lasting color

EASYSOAK™ (Umbriano)

Factory Sealed to provide integral stain resistance

COLOR FUSION™ (Umbriano)

Subtly mottled color finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

	3x12"	4x16"
Bundle Type	SINGLE	SINGLE
Plant Produced	NEW YORK	NEW YORK
Thickness (mm)	100 MM	100 MM

SQFT PER	Bundle	63.94	62.00
	Layer	10.66	10.33
	Section	-	-
	Stone	0.24	0.43

PER BUNDLE	Layers	6.00	6.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	1.02	0.76
	Section	-	-
	Layer	10.83	7.87
	Bundle	64.96	47.24


SAILOR LNFT PER	SqFt	4.06	3.05
	Section	-	-
	Layer	43.31	31.50
	Bundle	259.84	188.98

UNITS PER	SqFt	4.13	2.32
	Section	-	-
	Bundle	264.00	144.00

LBS PER	Layer	488	455
	Section	-	-
	Bundle	2,927	2,730

COLORS	Reflectance	Stock	Stock
Multiple Colors and Finishes	SR n/a SRI n/a	S0	S0

LAYING PATTERNS



Single Units

3x12"
 75 x 300 x 100mm
 3 x 11 7/8 x 3 7/8"
 220 units/Bundle
 .24 Sq.Ft./Stone

4x16"
 100 x 400 x 100mm
 3 7/8 x 15 3/4 x 3 7/8"
 120 units/Bundle
 .43 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
 Surface Texture - Smooth
 Joint Spacing - 6mm
 Void - 10.18%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

CLASSIC

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits



NATURAL

	CLASSIC FINISH
Bundle Type	SINGLE
Plant Produced	NEW YORK
Thickness (mm)	80 MM

SQFT PER	Bundle	67.00
	Layer	9.57
	Section	-
	Stone	0.27

PER BUNDLE	Layers	7.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-


SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	3.66
	Section	-
	Bundle	245.00

LBS PER	Layer	349
	Section	-
	Bundle	2,445

COLORS	Reflectance	Stock
Natural	SR n/a SRI n/a	SO

Single Unit



STANDARD
 115 x 230 x 80mm
 4 5/8 x 9 x 3 1/8"
 245 Units/Bundle
 .27 SqFt/Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



	8"X8" HEX	
Bundle Type	SINGLE	RANDOM
Plant Produced	ONTARIO	ONTARIO
Thickness (mm)	70 MM	60 MM

SQFT PER	Bundle	73.92	94.14
	Layer	9.24	10.46
	Section	-	-
	Stone	0.39	1.31

PER BUNDLE	Layers	8.00	9.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	-	-
	Section	-	-
	Layer	-	-
	Bundle	-	-

SAILOR LNFT PER	SqFt	-	0.85
	Section	-	-
	Layer	-	8.86
	Bundle	-	79.72

UNITS PER	SqFt	2.60	0.76
	Section	-	-
	Bundle	192.00	72.00

LBS PER	Layer	306	287
	Section	-	-
	Bundle	2,450	2,583

COLORS	Reflectance	Stock	Stock
Notte Hex	SR n/a SRI n/a	SO	
Sabia Hex	SR n/a SRI n/a	SO	
Notte Random	SR n/a SRI n/a		SO
Sabia Random	SR n/a SRI n/a		SO

APPLICATIONS



APPEARANCE

Edge Detail - Rounded
 Surface Texture - Granito/
 Granito Textured (Random)
 Joint Spacing - 7 mm

TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

ARTISTA™

Boldly mottled color finish



EASYSOAK™

Factory Sealed to provide integral stain resistance

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



Granito Hex



NOTTE HEX



SABIA HEX



NOTTE RANDOM



SABIA RANDOM

3-Unit Random Bundle		SMALL RECTANGLE 180 x 360 x 60mm 7 x 14 1/4 x 2 3/8" 27 units/Bundle .79 Sq.Ft./Stone		SQUARE 360 x 360 x 60mm 14 1/4 x 14 1/4 x 2 3/8" 27 units/Bundle 1.40 Sq.Ft./Stone		LARGE RECTANGLE 360 x 540 x 60mm 14 1/4 x 21 1/4 x 2 3/8" 18 units/Bundle 2.09 Sq.Ft./Stone	Single Unit		HEX 200 x 200 x 70mm 7 7/8 x 7 7/8 x 3 1/8" 192 units/Bundle .39 Sq.Ft./Stone
-----------------------------	---	--	---	---	---	--	--------------------	---	--

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro Surface Texture
Smooth/Exposed
Joint Spacing - 3 mm

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ENDURACOLOR™

Refined surface and long-lasting color

COLOR FUSION™ (Umbriano)

Subtly mottled color finish

EASYCLEAN™ (Umbriano)

Factory Sealed to provide integral stain resistance

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

	HEX	HEX PERMEABLE
Bundle Type	SINGLE	SINGLE
Plant Produced	NEW YORK	NEW YORK
Thickness (mm)	70 MM	80 MM

SQFT PER	Bundle	73.92	59.24
	Layer	9.24	8.46
	Section	-	-
	Stone	0.39	0.42

PER BUNDLE	Layers	8.00	7.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	-	-
	Section	-	-
	Layer	-	-
	Bundle	-	-


SAILOR LNFT PER	SqFt	-	-
	Section	-	-
	Layer	-	-
	Bundle	-	-

UNITS PER	SqFt	2.60	2.36
	Section	-	-
	Bundle	192.00	140.00

LBS PER	Layer	306	310
	Section	-	-
	Bundle	2,450	2,167

COLORS	Reflectance	Stock	Stock
Multiple Colors & Finishes	SR .n/a SRI n/a	SO	SO

LAYING PATTERNS



Hex Paver

Single Units



HEX
200 x 200 x 70mm
7 7/8 x 7 7/8 x 2 3/4"
192 Units/Bundle
.39 SqFt/Stone



HEX PERMEABLE
200 x 200 x 80mm
7 7/8 x 7 7/8 x 3 1/8"
140 Units/Bundle
.42 SqFt/Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
 Surface Texture - Smooth
 Joint Spacing - 3 mm


TECHNOLOGIES

CLASSIC
 Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



ALMOND GROVE



CHARCOAL



GRANITE

		SMOOTH
Bundle Type		SINGLE
Plant Produced		UXBRIDGE
Thickness (mm)		60 MM

SQFT PER	Bundle	106.20
	Layer	-
	Section	17.70
	Stone	0.22

PER BUNDLE	Layers	-
	Sections	6.00

SOLDIER LNFT PER	SqFt	1.50
	Section	26.57
	Layer	-
	Bundle	159.45

SAILOR LNFT PER	SqFt	3.00
	Section	53.15
	Layer	-
	Bundle	318.90

UNITS PER	SqFt	4.58
	Section	81.00
	Bundle	486.00

LBS PER	Layer	-
	Section	478
	Bundle	2,868

COLORS	Reflectance	Stock
Almond Grove	SR n/a SRI n/a	✓
Charcoal	SR .12 SRI 9	✓
Granite	SR .26 SRI 27	✓

Single Unit



4x8 STANDARD
 100 x 200 x 60mm
 3 7/8 x 7 7/8 x 2 3/8"
 486 units/Bundle
 .22 Sq.Ft./Stone

Important: A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
 Surface Texture - Smooth
 Joint Spacing - 3 mm


TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits.

LAYING PATTERNS



ALMOND GROVE



CHARCOAL



FOSSIL



STEEL MOUNTAIN

	SMOOTH FINISH
Bundle Type	SINGLE
Plant Produced	UXBRIDGE
Thickness (mm)	60 MM

SQFT PER	Bundle	106.2
	Layer	11.80
	Section	-
	Stone	0.22

PER BUNDLE	Layers	10.00
	Sections	-

SOLDIER LNFT PER	SqFt	1.50
	Section	-
	Layer	17.72
	Bundle	177.17

SAILOR LNFT PER	SqFt	3.00
	Section	-
	Layer	35.43
	Bundle	354.33

UNITS PER	SqFt	4.58
	Section	-
	Bundle	540.00

LBS PER	Layer	330
	Section	-
	Bundle	3,305

COLORS	Reflectance	Stock
Almond Grove	SR n/a sRI n/a	✓
Charcoal	SR n/a sRI n/a	✓
Fossil	SR .22 sRI 21	✓
Steel Mountain	SR n/a sRI n/a	✓

Single Unit



STANDARD
 100 x 200 x 60mm
 3 7/8 x 7 7/8 x 2 3/8"
 486 units/Bundle
 .22 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces.** All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
 Surface Texture - Il Campo Brushed
 Joint Spacing - 3 mm


TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



DARK CHARCOAL



GRANITE



LIGHT GREY

	4x8"	8x16"
Bundle Type	SINGLE	SINGLE
Plant Produced	ONTARIO	ONTARIO
Thickness (mm)	70 MM	70 MM

SQFT PER	Bundle	94.40	82.67
	Layer	11.80	10.33
	Section	-	-
	Stone	0.22	0.86

PER BUNDLE	Layers	8.00	8.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	1.50	0.76
	Section	-	-
	Layer	17.72	7.87
	Bundle	141.73	62.99

SAILOR LNFT PER	SqFt	3.00	1.52
	Section	-	-
	Layer	35.43	15.75
	Bundle	283.46	125.98

UNITS PER	SqFt	4.58	1.16
	Section	-	-
	Bundle	432.00	96.00

LBS PER	Layer	377	343
	Section	-	-
	Bundle	3,019	2,747

COLORS	Reflectance	Stock	Stock
Dark Charcoal	SR n/a SRI n/a	SO	SO
Granite	SR n/a SRI n/a		SO
Light Grey	SR .22 SRI 22		SO

Single Units



4x8
 100 x 200 x 70mm
 3⁷/₈ x 7⁷/₈ x 2³/₄"
 432 Units/Bundle
 .22 SqFt/Stone



8x16
 200 x 400 x 70mm
 7⁷/₈ x 15³/₄ x 2³/₄"
 96 Units/Bundle
 .86 SqFt/Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
 Surface Texture - Smooth
 Joint Spacing - 4 mm

TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

EASYCLEAN™

Factory Sealed to provide integral stain resistance


ANTIQUED™

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



	STANDARD SMOOTH
Bundle Type	SINGLE
Plant Produced	PICKERING
Thickness (mm)	70 MM

SQFT PER	Bundle	89.28
	Layer	11.16
	Section	-
	Stone	0.16

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	1.27
	Section	-
	Layer	14.17
	Bundle	113.39

SAILOR LNFT PER	SqFt	5.08
	Section	-
	Layer	56.69
	Bundle	453.54

UNITS PER	SqFt	6.45
	Section	-
	Bundle	576.00

LBS PER	Layer	357
	Section	-
	Bundle	2,859

COLORS	Reflectance	Stock
Dark Charcoal	SR n/a SRI n/a	✓
Granite Blend	SR n/a SRI n/a	✓
Sable Blend	SR n/a SRI n/a	✓



DARK CHARCOAL



GRANITE BLEND



SABLE BLEND

Single Unit



STANDARD
 60 x 240 x 70mm
 2 3/8 x 9 1/2 x 2 3/4"
 576 Units/Bundle
 .16 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information.



BRUSHED FINISH	12" X 24"	18" X 24"	24" X 24"	24" X 36"
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
Thickness (mm)	22 MM	22 MM	22 MM	22 MM

SQFT PER	Crate	180.00	186.00	160.00	180.00
	Units	2.00	3.00	4.00	6.00

UNITS PER	Crate	90.00	62.00	40.00	30.00
	SqFt	0.50	0.33	0.25	0.17

LBS PER	Unit	24	36	48	72
	Bundle	2,149	2,221	1,910	2,149

COLORS	Reflectance	Stock	Stock	Stock	Stock
Autumn Harvest (Riven)	SR n/a SRI n/a	✓	✓	✓	✓
Golden Sand (Brushed)	SR n/a SRI n/a	✓	✓	✓	✓
Ivory Sand (Brushed)	SR n/a SRI n/a	✓	✓	✓	✓
Stone Cliff Grey (Riven)	SR n/a SRI n/a	✓	✓	✓	✓

APPLICATIONS




APPEARANCE

Edge Detail - Zero
 Surface Texture - Brushed / Riven
 Joint Spacing - 0 mm

TECHNICAL INFORMATION

Visit Unilock.com for more information.

LAYING PATTERNS



AUTUMN HARVEST



GOLDEN SAND



IVORY SAND



STONE CLIFF GREY

Single Units				
	12 X 24"	18 X 24"	24 X 24"	24 X 36"
	300 x 600 x 22mm	450 x 600 x 22mm	600 x 600 x 22mm	600 x 900 x 22mm
	11 7/8 x 23 5/8 x 7/8"	17 3/4 x 23 5/8 x 7/8"	23 5/8 x 23 5/8 x 7/8"	23 5/8 x 35 1/2 x 7/8"
	2.0 Sq.Ft./Stone	3.0 Sq.Ft./Stone	4.0 Sq.Ft./Stone	6.0 Sq.Ft./Stone

Notes: This product is not intended for vehicular applications. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



		48 X 12" FULLNOSE COPING	48 X 12" ROCK FACED COPING	48 X 16" ROCK FACED COPING	72 X 12" FULLNOSE COPING	72 X 12" ROCK FACED COPING	72 X 16" ROCK FACED COPING
Bundle Type		SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Thickness (mm)		50 MM	50 MM	50 MM	50 MM	50 MM	50 MM

UNITS PER	Crate	20.00	20.00	20.00	12.00	12.00	10.00
	SqFt	-	-	-	-	-	-

LBS PER	Unit	106	101	113	159	159	209
	Bundle	2,116	2,028	2,258	1,905	1,905	2,094

COLORS	Reflectance	Stock	Stock	Stock	Stock	Stock	Stock
Autumn Harvest	SR n/a SRI n/a	✓	✓	✓	✓	✓	✓
Golden Sand	SR n/a SRI n/a	✓	✓	✓	✓	✓	✓
Ivory Sand	SR n/a SRI n/a	✓	✓	✓	✓	✓	✓
Stone Cliff Grey	SR n/a SRI n/a	✓	✓	✓	✓	✓	✓



AUTUMN HARVEST



GOLDEN SAND




IVORY SAND




STONE CLIFF GREY


Coping




4' FULLNOSE COPING
1,200 x 50 x 300mm
47 1/4 x 2 x 11 7/8"




6' FULLNOSE COPING
1,800 x 50 x 300mm
70 7/8 x 2 x 11 7/8"




4' ROCK FACE COPING
1,200 x 50 x 300mm
47 1/4 x 2 x 11 7/8"



6' ROCKFACE COPING
1,800 x 50 x 300mm
70 7/8 x 2 x 11 7/8"



4' ROCK FACE COPING
1,200 x 50 x 400mm
47 1/4 x 2 x 15 3/4"



6' ROCKFACE COPING
1,800 x 50 x 400mm
70 7/8 x 2 x 15 3/4"



	24 X 24" ROCK FACED PILLAR CAP	29 X 29" ROCK FACED PILLAR CAP	48 X 16" ROCK FACED STEP	72 X 16" ROCK FACED STEP
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
Thickness (mm)	64 MM	64 MM	150 MM	150 MM

FCFT PER	Crate	-	-	32.00	32.00
-----------------	-------	---	---	-------	-------

LNFT PER	Crate	-	-	24.00	24.00
	Unit	-	-	4.00	6.00

UNITS PER	Crate	14.00	12.00	6.00	4.00
------------------	-------	-------	-------	------	------

LBS PER	Unit	137	209	421	628
	Bundle	1,914	2,513	2,526	2,513

COLORS	Reflectance	Stock	Stock	Stock	Stock
Autumn Harvest	SR n/a SRI n/a	✓	✓	✓	✓
Golden Sand	SR n/a SRI n/a	✓	✓	✓	✓
Ivory Sand	SR n/a SRI n/a	✓	✓	✓	✓
Stone Cliff Grey	SR n/a SRI n/a	✓	✓	✓	✓

APPLICATIONS



APPEARANCE

Edge Detail - Zero

Surface Texture - Brushed / Riven

Joint Spacing - 0 mm

TECHNICAL INFORMATION

Visit Unilock.com for more information.



AUTUMN HARVEST



GOLDEN SAND



IVORY SAND



STONE CLIFF GREY

Steps		48 X 16" STEP 1,200 x 150 x 400mm 47 1/4 x 5 7/8 x 15 3/4"		72 X 16" STEP 1,830 x 150 x 400mm 72 x 5 7/8 x 15 3/4"	Pillar Caps		PILLAR CAP 600 x 600 x 64mm 23 5/8 x 23 5/8 x 2 5/8"		PILLAR CAP 725 x 725 x 64mm 28 5/8 x 28 5/8 x 2 5/8"
-------	--	---	--	---	-------------	--	---	--	---

Notes: This product is not intended for vehicular applications. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS




APPEARANCE

Edge Detail - Zero
 Surface Texture - Riven
 Joint Spacing - 0 mm
 Void - 0 %

TECHNICAL INFORMATION

Visit Unilock.com for more information.

LAYING PATTERNS



BLACK RIVER



HEARTHSTONE



WINTER MIST

	12" X 24"	18" X 24"	24" X 24"	24" X 36"
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
Thickness (mm)	22 MM	22 MM	22 MM	22 MM

SQFT PER	Crate	180.00	186.00	160.00	180.00
	Units	2.00	3.00	4.00	6.00

UNITS PER	Crate	90.00	62.00	40.00	30.00
	SqFt	0.50	0.33	0.25	0.17

LBS PER	Unit	24	36	48	72
	Bundle	2,149	2,221	1,910	2,149

COLORS	Reflectance	Stock	Stock	Stock	Stock
Black River	SR n/a SRI n/a	✓	✓	✓	✓
Hearthstone	SR n/a SRI n/a	✓	✓	✓	✓
Winter Mist	SR n/a SRI n/a	✓	✓	✓	✓

Single Units



12 X 24"
 300 x 600 x 22mm
 11 7/8 x 23 5/8 x 7/8"
 2.0 Sq.Ft./Stone



18 X 24"
 450 x 600 x 22mm
 17 3/4 x 23 5/8 x 7/8"
 3.0 Sq.Ft./Stone



24 X 24"
 600 x 600 x 22mm
 23 5/8 x 23 5/8 x 7/8"
 4.0 Sq.Ft./Stone



24 X 36"
 600 x 900 x 22mm
 23 5/8 x 35 1/2 x 7/8"
 6.0 Sq.Ft./Stone

Notes: Due to natural oxidation, the Black River Limestone will require sealing to maintain its deep rich color. Unilock recommends a solvent-based sealer for natural stone. All measurement are nominal. Product is not intended for vehicular applications.



APPLICATIONS



BLACK RIVER



HEARTHSTONE



WINTER MIST

		48 X 12" ROCKFACED COPING	48 X 16" ROCK FACED COPING	72 X 12" ROCK FACED COPING	72 X 16" ROCK FACED COPING	48-X 12" FULLNOSE COPING	72 X 12" FULLNOSE COPING
Bundle Type		SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Thickness (mm)		50 MM	50 MM	50 MM	50 MM	50 MM	50 MM
UNITS PER	Crate	20.00	16.00	12.00	10.00	20.00	12.00
	SqFt	-	-	-	-	-	-
LBS PER	Unit	106	141	159	209	159	159
	Bundle	2,116	2,258	1,905	2,094	3,175	1,905
COLORS	Reflectance	Stock	Stock	Stock	Stock	Stock	Stock
Black River	SR n/a SRI n/a	✓	✓	✓	✓	✓	✓

		24 X 24" ROCK FACED PILLAR CAP	28 X 28" ROCK FACED PILLAR CAP	48 X 16" ROCK FACED STEP	72 X 16" ROCK FACED STEP
Bundle Type		SINGLE	SINGLE	SINGLE	SINGLE
Thickness (mm)		64 MM	64 MM	150 MM	150 MM
FCFT PER	Crate	-	-	-	-
LNFT PER	Crate	-	-	24.00	24.00
	Unit	-	-	4.00	6.00
UNITS PER	Crate	14.00	12.00	6.00	4.00
LBS PER	Unit	137	186	421	628
	Bundle	1,914	2,606	2,526	2,513
COLORS	Reflectance	Stock	Stock	Stock	Stock
Black River	SR n/a SRI n/a	✓	✓	✓	✓
Hearthstone	SR n/a SRI n/a	✓	✓		
Winter Mist	SR n/a SRI n/a	✓	✓		

48" & 72" Steps		48 X 16" STEP 1,200 x 150 x 400mm 47 1/4 x 5 7/8 x 15 3/4"		72 X 16" STEP 1,800 x 150 x 400mm 70 7/8 x 5 7/8 x 15 3/4"
	Pillar Caps		24" PILLAR CAP 600 x 600 x 64mm 23 5/8 x 23 5/8 x 2 5/8"	
Coping			48 X 12" ROCK FACE 1,200 x 300 x 50mm 47 1/4 x 11 7/8 x 2"	
		48 X 16" ROCK FACE 400 x 1,200 x 50mm 47 1/4 x 15 3/4 x 2"		72 X 16" ROCK FACE 1,800 x 400 x 50mm 47 1/4 x 15 3/4 x 2"
		48 X 12" FULLNOSE 300 x 1,200 x 50mm 11 7/8 x 47 1/4 x 2"		72 X 12" FULLNOSE 1,800 x 300 x 50mm 70 7/8 x 11 7/8 x 2"

Notes: Due to natural oxidation, the Black River Limestone will require sealing to maintain its deep rich color. Unilock recommends a solvent-based sealers for natural stone. All measurements are nominal. Product is not intended for vehicular applications.



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Series Exposed Textured

Joint Spacing - mm

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits

	TRAPEZOID
Bundle Type	SINGLE
Plant Produced	CHICAGO
Thickness (mm)	60 MM

SQFT PER	Bundle	78.60
	Layer	9.83
	Section	-
	Stone	0.05

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	3.39
	Section	-
	Layer	33.31
	Bundle	266.46


SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	21.98
	Section	-
	Bundle	1,728.00


LBS PER	Layer	223
	Section	-
	Bundle	1,786

COLORS	Reflectance	Stock
Cobalt Gray	SR n/a SRI n/a	✓
Onyx Black	SR n/a SRI n/a	✓


LAYING PATTERNS



NordicCobble_A



NordicCobble_Fan



NordicCobble_Circle



COBALT GRAY



ONYX BLACK

Single Unit



STANDARD

89.9 x 94 x 60mm

3 5/8 x 3 3/4 x 2 3/8"

864 units/Bundle

.05 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces.** All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
 Surface Texture - Smooth
 Joint Spacing - 8 mm

TECHNOLOGIES

CLASSIC
 Budget-friendly traditional product mix

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

	SMOOTH CLASSIC / ENDURACOLOR
Bundle Type	SINGLE
Plant Produced	UXB/NY
Thickness (mm)	80 MM

SQFT PER	Bundle	67.66
	Layer	9.67
	Section	-
	Stone	0.54

PER BUNDLE	Layers	7.00
	Sections	-

SOLDIER LNFT PER	SqFt	1.59
	Section	-
	Layer	15.35
	Bundle	107.48


SAILOR LNFT PER	SqFt	1.59
	Section	-
	Layer	15.35
	Bundle	107.48

UNITS PER	SqFt	1.86
	Section	-
	Bundle	126.00

LBS PER	Layer	359
	Section	-
	Bundle	2,516

COLORS	Reflectance	Stock
Natural	SR n/a SRI n/a	SO
Granite	SR n/a SRI n/a	SO

LAYING PATTERNS



NATURAL



GRANITE

Single Unit

STANDARD
 100 x 200 x 80mm
 3 7/8 x 7 7/8 x 3 1/8"
 378 units/Bundle
 .22 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.

Porcelain



APPLICATIONS



APPEARANCE

Edge Detail - n/a
 Surface Texture - Stone Finish
 Joint Spacing - n/a

TECHNICAL INFORMATION

Visit Unilock.com for more information.

LAYING PATTERNS



		DEL CONCA 24x24" PRESSED EDGE	DEL CONCA 16x32" PRESSED EDGE	DEL CONCA COPING POOL PRESSED EDGE
Bundle Type		SINGLE	SINGLE	SINGLE
Plant Produced				
Thickness (mm)		20 MM	20 MM	30 MM
SQFT PER	Pallet	255.75	268.71	-
	Box	7.75	6.89	-
	Unit	3.88	3.45	-
PER PALLET	Box	33.00	39.00	38.00
	SqFt	255.75	268.71	-
	Unit	66.00	78.00	38.00
UNITS PER	Pallet	66.00	78.00	38.00
	Box	2.00	2.00	1.00
LBS PER	Unit	35	32	30
	SqFt	9	9	-
	Box	70	64	30
	Pallet	2,318	2,511	1,127

COLORS	Reflectance	Stock	Stock	Stock
Gotham Bianco	SR n/a SRI n/a	✓		
Gotham Grey	SR n/a SRI n/a	✓		✓
Gotham Nero	SR n/a SRI n/a	✓		
Quartzite Dark Gray	SR n/a SRI n/a		✓	
Quartzite Sand	SR n/a SRI n/a		✓	
Travstone Beige	SR n/a SRI n/a	✓		



GOTHAM BIANCO



GOTHAM GREY




GOTHAM NERO



QUARTZITE DARK GRAY



QUARTZITE SAND



TRAVSTONE BEIGE

Single Units		DEL CONCA 24x24 600 x 600 x 20mm 23 5/8 x 23 5/8 x 7/8" 3.88 Sq.Ft./Stone		DEL CONCA 16x32 400 x 800 x 20mm 15 3/4 x 31 1/2 x 7/8" 3.45 Sq.Ft./Stone		DEL CONCA COPING 330 x 600 x 30mm 13 x 23 5/8 x 1 1/4"
--------------	---	---	---	---	---	---

Notes: All measurements are nominal. Contact Unilock for more information. Porcelain tile is not covered by Unilock's Lifetime Guarantee. Please contact your Territory Manager for more information. Product is not intended for vehicular applications.



	3 X 12	4 X 12	4 X 16	8 X 24
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	NEW YORK	NEW YORK	NEW YORK	NEW YORK
Thickness (mm)	100 MM	100 MM	100 MM	100 MM

SQFT PER	Bundle	63.94	69.76	62.00	62.00
	Layer	10.66	11.63	10.33	10.33
	Section	-	-	-	-
	Stone	0.24	0.32	0.43	1.29

PER BUNDLE	Layers	6.00	6.00	6.00	6.00
	Sections	-	-	-	-

SOLDIER LNFT PER	SqFt	1.35	1.02	0.76	0.51
	Section	-	-	-	-
	Layer	14.44	11.81	7.87	5.25
	Bundle	86.61	70.87	47.24	31.50

SAILOR LNFT PER	SqFt	4.06	3.05	3.05	1.52
	Section	-	-	-	-
	Layer	43.31	35.43	31.50	15.75
	Bundle	259.84	212.60	188.98	94.49

UNITS PER	SqFt	4.13	3.10	2.32	0.77
	Section	-	-	-	-
	Bundle	264.00	216.00	144.00	48.00

LBS PER	Layer	483	532	455	478
	Section	-	-	-	-
	Bundle	2,898	3,191	2,730	2,869

COLORS	Reflectance		Stock	Stock	Stock	Stock
Multiple Colors and Finishes	SR n/a	SRI n/a	S0	S0	S0	S0

Different finishes available by Special Order.
Please contact your Territory Manager for more details.

APPLICATIONS



APPEARANCE

Edge Detail - Rounded
Surface Texture - Smooth & Series™ Exposed
Joint Spacing - 4 mm

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

EASYCLEAN™ (Umbriano)

Factory Sealed to provide integral stain resistance


COLOR FUSION™ (Umbriano)

Subtly mottled color finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
Eligible for LEED v4.1 credits

LAYING PATTERNS



Single Units	3" X 12" 100 x 300 x 100mm 3 7/8 x 11 7/8 x 3 7/8" 264 units/Bundle .24 Sq.Ft./Stone	4" X 12" 100 x 300 x 100mm 3 7/8 x 11 7/8 x 3 7/8" 216 units/Bundle .32 Sq.Ft./Stone	4" X 16" 100 x 400 x 100mm 3 7/8 x 15 3/4 x 3 7/8" 144 units/Bundle .43 Sq.Ft./Stone	8" X 24" 200 x 600 x 100mm 7 7/8 x 23 5/8 x 3 7/8" 48 units/Bundle 1.29 Sq.Ft./Stone

Notes: **Special Order - Lead time required.** Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces.** All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
 Surface Texture - Smooth
 Joint Spacing

TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

	4 X 8	8 X 24
Bundle Type	SINGLE	SINGLE
Plant Produced	UXBRIDGE	UXBRIDGE
Thickness (mm)	70 MM	70 MM

SQFT PER	Bundle	94.40	82.67
	Layer	11.80	10.33
	Section	-	-
	Stone	0.22	1.29

PER BUNDLE	Layers	8.00	8.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	1.50	0.51
	Section	-	-
	Layer	17.72	5.25
	Bundle	141.73	41.99


SAILOR LNFT PER	SqFt	3.00	1.02
	Section	-	-
	Layer	35.43	10.50
	Bundle	283.46	83.99

UNITS PER	SqFt	4.58	0.77
	Section	-	-
	Bundle	432.00	64.00

LBS PER	Layer	334	331
	Section	-	-
	Bundle	2,669	2,647

COLORS	Reflectance	Stock	Stock
Dark Charcoal	SR n/a SRI n/a	✓	
Tuscany	SR n/a SRI n/a	✓	✓

LAYING PATTERNS



DARK CHARCOAL



TUSCANY

Single Units



4" X 8"
 100 x 200 x 70mm
 3 7/8 x 7 7/8 x 2 3/4"
 432 units/Bundle
 .22 Sq.Ft./Stone



8" X 24"
 200 x 600 x 70mm
 7 7/8 x 23 5/8 x 2 3/4"
 64 units/Bundle
 1.29 Sq.Ft./Stone



APPLICATIONS



APPEARANCE

Edge Detail - n/a
 Surface Texture - Textured
 Joint Spacing - 10 mm

TECHNOLOGIES

ELEGANCE™

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

EASYCLEAN™

Factory Sealed to provide integral stain resistance

REALA™

Cast from natural stone


ULTIMA™

Up to 4x stronger than poured-in-place concrete

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



	Bundle Type	RANDOM
	Plant Produced	AYR
	Thickness (mm)	60 MM

SQFT PER	Bundle	90.30
	Layer	11.29
	Section	-
	Stone	0.56

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	1.31
	Section	-
	Layer	14.78
	Bundle	118.22

UNITS PER	SqFt	1.77
	Section	-
	Bundle	160.00

LBS PER	Layer	309
	Section	-
	Bundle	2,472

COLORS	Reflectance	Stock
Dawn Mist	SR n/a SRI n/a	✓
Pebble Taupe	SR n/a SRI n/a	✓



DAWN MIST



PEBBLE TAUPE

3 Unit Random Bundle		RECTANGLE 226 x 300 x 60mm 8 7/8 x 11 7/8 x 2 3/8" 64 Units/Bundle .75 SqFt/Stone		SQUARE 226 x 226 x 60mm 8 7/8 x 8 7/8 x 2 3/8" 32 units/Bundle .58 Sq.Ft./Stone		SMALL RECTANGLE 150 x 226 x 60mm 5 7/8 x 8 7/8 x 2 3/8" 64 units/Bundle .38 Sq.Ft./Stone
----------------------	--	--	--	--	--	---

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. The Large Rectangle unit is not intended for vehicular applications. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Chamfer
 Surface Texture - Series Exposed
 Joint Spacing - 3 mm

TECHNOLOGIES


ENDURACOLOR™
 Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

		4 X 8	
Bundle Type		RANDOM	SINGLE
Plant Produced		NEW YORK	NEW YORK
Thickness (mm)		60 MM	70 MM
SQFT PER	Bundle	94.40	94.40
	Layer	11.80	11.80
	Section	-	-
	Stone	0.22	0.22
PER BUNDLE	Layers	8.00	8.00
	Sections	-	-
SOLDIER LNFT PER	SqFt	-	1.50
	Section	-	-
	Layer	-	17.72
	Bundle	-	141.76
SAILOR LNFT PER	SqFt	1.50	3.00
	Section	-	-
	Layer	17.72	35.43
	Bundle	141.76	283.44
UNITS PER	SqFt	3.00	4.58
	Section	-	-
	Bundle	35.43	432.00
LBS PER	Layer	377	377
	Section	-	-
	Bundle	3,019	3,019
COLORS		Reflectance	Stock
Black Granite		SR n/a SRI n/a	SO ✓

LAYING PATTERNS



BLACK GRANITE

Random Bundle				Single Unit
		LARGE RECTANGLE 360 x 540 x 60mm 14 1/4 x 21 1/4 x 2 3/8" 18 units/Bundle 2.09 Sq.Ft./Stone		SQUARE 360 x 360 x 60mm 14 1/4 x 14 1/4 x 2 3/8" 27 units/Bundle 1.40 Sq.Ft./Stone
		SMALL RECTANGLE 180 x 360 x 60mm 7 x 14 1/4 x 2 3/8" 27 units/Bundle .70 Sq.Ft./Stone		
				4x8" 100 x 200 x 70mm 3 7/8 x 7 7/8 x 2 3/4" 486 units/Bundle .22 Sq.Ft./Stone

Notes: For Special Order items - Lead time required. Minimum quantities apply. **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
 Surface Texture - Smooth
 Joint Spacing - 11-18 mm
 Void - 4.4%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

	SMOOTH
Bundle Type	RANDOM
Plant Produced	UXBRIDGE
Thickness (mm)	70 MM

SQFT PER	Bundle	88.61
	Layer	11.08
	Section	-
	Stone	0.92

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-


SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	1.08
	Section	-
	Bundle	96.00

LBS PER	Layer	355
	Section	-
	Bundle	2,838

COLORS	Reflectance	Stock
Fossil	SR .22 SRI 21	✓
New York Blend	SR n/a SRI n/a	✓
Steel Mountain	SR .30 SRI 31	✓

LAYING PATTERNS



FOSSIL



NEW YORK BLEND



STEEL MOUNTAIN

3 Unit Random Bundle



LARGE RECTANGLE
 350 x 420 x 70mm
 13 7/8 x 16 5/8 x 2 3/4"
 32 Units/Bundle



MEDIUM RECTANGLE
 210 x 350 x 70mm
 8 3/8 x 13 7/8 x 2 3/4"
 32 units/Bundle



SMALL RECTANGLE
 173 x 210 x 70mm
 6 7/8 x 8 3/8 x 2 3/4"
 32 units/Bundle

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - n/a
 Surface Texture - Textured
 Joint Spacing - 10 mm
 Void - 6.5%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ELEGANCE™

Timeless, long-lasting beauty with the combination of Reala and Ultima technologies

EASYCLEAN™ 

Factory Sealed to provide integral stain resistance

REALA™

Cast from historical brick


ULTIMA™

Up to 4x stronger than poured-in-place concrete

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



BASALT



BURGUNDY RED



BURNT CLAY



OLD OAK

	STANDARD
Bundle Type	SINGLE
Plant Produced	AYR
Thickness (mm)	60 MM

SQFT PER	Bundle	88.41
	Layer	11.05
	Section	-
	Stone	0.28

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	1.19
	Section	-
	Layer	13.12
	Bundle	104.99

SAILOR LNFT PER	SqFt	2.97
	Section	-
	Layer	32.81
	Bundle	262.47

UNITS PER	SqFt	3.62
	Section	-
	Bundle	320.00

LBS PER	Layer	361
	Section	-
	Bundle	2,888

COLORS	Reflectance	Stock
Burgundy Red	SR n/a SRI n/a	✓
Burnt Clay	SR n/a SRI n/a	✓
Old Oak	SR n/a SRI n/a	✓
Basalt	SR n/a SRI n/a	✓

Single Unit



STANDARD
 250 x 100 x 70mm
 9 7/8 x 3 7/8 x 2 3/4"
 300 units/Bundle
 .28 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
 Surface Texture - Textured
 Joint Spacing - 3 mm


TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



ALMOND GROVE



CHARCOAL



FOSSIL



NEW YORK BLEND



STEEL MOUNTAIN

		FLAGSTONE FINISH
Bundle Type		SINGLE
Plant Produced		UXBRIGE
Thickness (mm)		60 MM

SQFT PER	Bundle	125.00
	Layer	12.50
	Section	-
	Stone	0.42

PER BUNDLE	Layers	10.00
	Sections	-

SOLDIER LNFT PER	SqFt	1.18
	Section	-
	Layer	14.76
	Bundle	147.64

SAILOR LNFT PER	SqFt	1.81
	Section	-
	Layer	22.64
	Bundle	226.38

UNITS PER	SqFt	2.40
	Section	-
	Bundle	300.00

LBS PER	Layer	350
	Section	-
	Bundle	3,500

COLORS	Reflectance	Stick
Almond Grove	SR n/a SRI n/a	✓
Charcoal	SR n/a SRI n/a	✓
Fossil	SR n/a SRI n/a	✓
New York Blend	SR n/a SRI n/a	✓
Steel Mountain	SR n/a SRI n/a	✓

Single Unit



RECTANGLE
 150 x 230 x 60mm
 5 7/8" x 9 x 2 3/8"
 270 Units/Bundle
 .42 SqFt/Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting.** All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
 Surface Texture - Textured
 Joint Spacing - 4mm

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



ALMOND GROVE CHARCOAL FOSSIL NEW YORK BLEND STEEL MOUNTAIN

	FLAGSTONE ENDURACOLOR	FLAGSTONE
Bundle Type	RANDOM	SMALL RECTANGLE
Plant Produced	UXBRIGE	UXBRIGE
Thickness (mm)	60 MM	60 MM

SQFT PER	Bundle	118.90	118.90
	Layer	11.89	11.89
	Section	-	-
	Stone	0.48	0.30

PER BUNDLE	Layers	10.00	10.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	-	1.30
	Section	-	-
	Layer	-	15.42
	Bundle	-	154.20

SAILOR LNFT PER	SqFt	1.78	2.59
	Section	-	-
	Layer	21.19	30.84
	Bundle	211.90	308.40

UNITS PER	SqFt	2.10	3.36
	Section	-	-
	Bundle	250.00	400.00

LBS PER	Layer	320	316
	Section	-	-
	Bundle	3,203	3,161

COLORS	Reflectance	Stock	Stock
Almond Grove	SR .25 SRI 25	✓	✓
Charcoal	SR n/a SRI n/a		✓
Fossil	SR .22 SRI 21	✓	✓
New York Blend	SR n/a SRI n/a	✓	✓
Steel Mountain	SR .30 SRI 31	✓	✓

Random Bundle				Single Unit	
	<p>LARGE RECTANGLE 233 x 349.5 x 60mm 9 1/4 x 13 3/4 x 2 3/8" 50 units/Bundle .82 Sq.Ft./Stone</p>	<p>SQUARE 233 x 233 x 60mm 9 1/4 x 9 1/4 x 2 3/8" 60 units/Bundle .55 Sq.Ft./Stone</p>	<p>SMALL RECTANGLE 116.5 x 233 x 60mm 4 5/8 x 9 1/4 x 2 3/8" 130 units/Bundle .27 Sq.Ft./Stone</p>		<p>SMALL RECTANGLE 117.5 x 235 x 60mm 4 5/8 x 9 1/4 x 2 3/8" 400 units/Bundle .27 Sq.Ft./Stone</p>

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces.** Please refer to the Polymeric Sand Best Practices and Important Notice on page 97. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Rounded
 Surface Texture - Smooth
 Joint Spacing - 7mm
 Void - 5.5%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

	SMOOTH FINISH	SMOOTH FINISH
Bundle Type	RANDOM	RECTANGLE
Plant Produced	UXBRIDGE	UXBRIDGE
Thickness (mm)	60 MM	60 MM

SQFT PER	Bundle	116.87	116.87
	Layer	11.69	11.69
	Section	-	-
	Stone	0.56	0.56

PER BUNDLE	Layers	10.00	10.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	-	1.31
	Section	-	-
	Layer	-	15.29
	Bundle	-	152.89


SAILOR LNFT PER	SqFt	1.57	2.62
	Section	-	-
	Layer	18.35	30.58
	Bundle	183.46	305.77

UNITS PER	SqFt	1.80	3.42
	Section	-	-
	Bundle	210.00	400.00

LBS PER	Layer	321	321
	Section	-	-
	Bundle	3,208	3,208

COLORS	Reflectance	Stock	Stock
Almond Grove	SR n/a SRI n/a	✓	✓
Fossil	SR .22 SRI 21	✓	✓
New York Blend	SR n/a SRI n/a	✓	✓
Steel Mountain	SR .30 SRI 31	✓	✓

LAYING PATTERNS



ALMOND GROVE



FOSSIL



NEW YORK BLEND



STEEL MOUNTAIN

Random Bundle		LARGE RECTANGLE 233 x 349.5 x 60mm 9 1/4 x 13 3/4 x 2 3/8" 60 units/Bundle .82 Sq.Ft./Stone		SQUARE 233 x 233 x 60mm 9 1/4 x 9 1/4 x 2 3/8" 70 units/Bundle .55 Sq.Ft./Stone		SMALL RECTANGLE 116.5 x 233 x 60mm 4 5/8 x 9 1/4 x 2 3/8" 80 units/Bundle .27 Sq.Ft./Stone	Sold Separately		RECTANGLE 116.5 x 233 x 60mm 4 5/8 x 9 1/4 x 2 3/8" 400 units/Bundle .29 Sq.Ft./Stone
---------------	---	--	---	--	---	---	-----------------	---	--

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



	CURB	
Bundle Type	SINGLE	RANDOM
Plant Produced	NEW YORK	NEW YORK
Thickness (mm)	180 MM	70 MM

SQFT PER	Bundle	-	97.53
	Layer	-	12.19
	Section	-	-
	Stone	-	0.32

PER BUNDLE	Layers	3.00	8.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	-	-
	Section	-	-
	Layer	12.24	-
	Bundle	36.72	-

SAILOR LNFT PER	SqFt	-	2.34
	Section	-	-
	Layer	-	28.49
	Bundle	-	227.95

UNITS PER	SqFt	-	3.12
	Section	-	-
	Bundle	36.00	304.00

LBS PER	Layer	555	398
	Section	-	-
	Bundle	1,664	3,186

COLORS	Reflectance	Stock	Stock
Crystalline Basalt	SR n/a SRI n/a	✓	✓
Peppered Granite	SR .38 SRI 42	✓	✓

APPLICATIONS



APPEARANCE

Edge Detail - Micro

Surface Texture - Series Exposed Textured

Joint Spacing - 10mm

Void - 5.6%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ENDURACOLOR™



Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936

Eligible for LEED v4.1 credits

LAYING PATTERNS



CRYSTALLINE BASALT

PEPPERED GRANITE

Random Bundle		LARGE RECTANGLE 130 x 305 x 70mm 5 x 12 x 2 ¾" 88 units/Bundle .43 Sq.Ft./Stone		RECTANGLE 130 x 230 x 70mm 5 x 9 x 2 ¾" 88 units/Bundle .32 Sq.Ft./Stone		SMALL RECTANGLE 130 x 175 x 70mm 5 x 6 7/8 x 2 ¾" 128 units/Bundle .25 Sq.Ft./Stone	Single Unit		CURB 230 x 290 x 180mm 9 x 11 ½ x 7" 36 units/Bundle
---------------	---	--	---	---	---	--	-------------	---	--

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. For permeable installations, Unilock recommends using granite chips for joint filler. For traditional applications, please refer to the Polymeric Sand Best Practices on page 97. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

- Edge Detail - Zero
- Surface Texture - Smooth
- Joint Spacing - 2mm
- Void - 40%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

CLASSIC

Budget-friendly traditional product mix

TECHNICAL INFORMATION

- Conforms to ASTM C1319
- Eligible for LEED v4.1 credits

	CLASSIC FINISH
Bundle Type	RANDOM
Plant Produced	UXBRIDGE
Thickness (mm)	80 MM

SQFT PER	Bundle	72.00
	Layer	10.29
	Section	-
	Stone	2.57

PER BUNDLE	Layers	7.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-


SAILOR LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

UNITS PER	SqFt	0.39
	Section	-
	Bundle	28.00

LBS PER	Layer	250
	Section	-
	Bundle	1,748

COLORS	Reflectance	Stock
Natural	SR .30 SRI 32	✓

LAYING PATTERNS



Turfstone Fixed Random



NATURAL

Single Unit



LARGE RECTANGLE
 400 x 600 x 80mm
 15 3/4 x 23 5/8 x 3 1/8"
 28 units/Bundle
 2.57 Sq.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Micro
 Surface Texture - Umbriano Mottled
 Joint Spacing - 7mm

TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

EASYSOAK™

Factory Sealed to provide integral stain resistance



COLORFUSION™

Subtly mottled colored finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



FRENCH GREY



MIDNIGHT SKY



SUMMER WHEAT



WINTER MARVEL

		UMBRIANO FINISH
	Bundle Type	RANDOM
	Plant Produced	NEW YORK
	Thickness (mm)	60 MM

SQFT PER	Bundle	104.60
	Layer	10.46
	Section	-
	Stone	1.31

PER BUNDLE	Layers	10.00
	Sections	-

SOLDIER LNFT PER	SqFt	-
	Section	-
	Layer	-
	Bundle	-

SAILOR LNFT PER	SqFt	0.82
	Section	-
	Layer	8.61
	Bundle	86.12

UNITS PER	SqFt	0.76
	Section	-
	Bundle	80.00

LBS PER	Layer	305
	Section	-
	Bundle	3,050

COLORS	Reflectance	Stock
French Grey	SR .18 SRI 17	✓
Midnight Sky	SR .17 SRI 15	SO
Summer Wheat	SR .42 SRI 48	✓
Winter Marvel	SR .35 SRI 38	✓

Random Bundle



LARGE RECTANGLE
 360 x 540 x 60mm
 14 1/4 x 21 1/4 x 2 3/8"
 20 units/Bundle



SQUARE
 360 x 360 x 60mm
 14 1/4 x 14 1/4 x 2 3/8"
 30 units/Bundle



SMALL RECTANGLE
 180 x 360 x 60mm
 7 x 14 1/4 x 2 3/8"
 30 units/Bundle

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. This product is not intended for vehicular use. All measurements are nominal. Contact Unilock for more information.

Umbriano® 70mm



APPLICATIONS



APPEARANCE

Edge Detail - Zero
 Surface Texture - Umbriano Mottled
 Joint Spacing - 7mm

TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

EASYSOAK™

Factory Sealed to provide integral stain resistance

COLORFUSION™

Subtly mottled colored finish

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

	8x16	12x24	16x16	24x24
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	NEW YORK	NEW YORK	NEW YORK	NEW YORK
Thickness (mm)	70 MM	70 MM	70 MM	70 MM

SQFT PER	Bundle	82.67	93.00	82.67	62.00
	Layer	10.33	11.63	10.33	7.75
	Section	-	-	-	-
	Stone	0.86	1.94	1.72	3.88

PER BUNDLE	Layers	8.00	8.00	8.00	8.00
	Sections	-	-	-	-

SOLDIER LNFT PER	SqFt	0.76	0.51	0.76	0.51
	Section	-	-	-	-
	Layer	7.87	5.91	7.87	3.94
	Bundle	62.99	47.24	62.99	31.50

SAILOR LNFT PER	SqFt	1.52	1.02	0.76	0.51
	Section	-	-	-	-
	Layer	15.75	11.81	7.87	3.94
	Bundle	125.98	94.49	62.99	31.50

UNITS PER	SqFt	1.16	0.52	0.58	0.26
	Section	-	-	-	-
	Bundle	96.00	48.00	48.00	16.00

LBS PER	Layer	331	372	331	258
	Section	-	-	-	-
	Bundle	2,646	2,978	2,646	2,055

COLORS	Reflectance	Stock	Stock	Stock	Stock
French Grey	SR .18 SRI 17	SO	SO	SO	SO
Midnight Sky	SR .17 SRI 15	SO	SO	SO	SO
Summer Wheat	SR .42 SRI 48	SO	SO	SO	SO
Winter Marvel	SR .35 SRI 38	SO	SO	SO	SO

LAYING PATTERNS



FRENCH GREY



MIDNIGHT SKY



SUMMER WHEAT



WINTER MARVEL

Single Units	8 x 16	12 x 24	16 x 16	24 x 24
	200 x 400 x 70mm 7 7/8 x 15 3/4 x 2 3/4" 96 units/Bundle .86 Sq.Ft./Stone	300 x 600 x 70mm 11 7/8 x 23 5/8 x 2 3/4" 48 units/Bundle 1.94 Sq.Ft./Stone	400 x 400 x 70mm 15 3/4 x 15 3/4 x 2 3/4" 48 units/Bundle 1.72 Sq.Ft./Stone	600 x 600 x 70mm 23 5/8 x 23 5/8 x 2 3/4" 16 units/Bundle 3.88 Sq.Ft./Stone

Notes: **Special Order items, lead time is required. SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces.**
 All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
 Surface Texture - Textured
 Joint Spacing - 3-7mm

TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

EASYCLEAN™

Factory Sealed to provide integral stain resistance


COMFORT STEP™

Ultra-smooth surface texture

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

LAYING PATTERNS



		5x10
Bundle Type	RANDOM	SINGLE
Plant Produced	UXBRIDGE	UXBRIDGE
Thickness (mm)	70 MM	70 MM

SQFT PER	Bundle	94.19	94.19
	Layer	11.77	11.77
	Section	-	-
	Stone	0.59	0.34

PER BUNDLE	Layers	8.00	8.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	-	1.24
	Section	-	-
	Layer	-	14.58
	Bundle	-	116.64

SAILOR LNFT PER	SqFt	1.24	2.48
	Section	-	-
	Layer	14.57	29.16
	Bundle	116.56	233.28

UNITS PER	SqFt	1.70	2.97
	Section	-	-
	Bundle	160.00	280.00

LBS PER	Layer	373	373
	Section	-	-
	Bundle	2,985	2,985

COLORS	Reflectance	Stock	Stock
Charcoal	SR.n/a SRI n/a		✓
Fossil	SR n/a SRI n/a	✓	✓
Steel Mountain	SR n/a SRI n/a	✓	✓
Walnut	SR n/a SRI n/a	✓	✓



CHARCOAL



FOSSIL



STEEL MOUNTAIN



WALNUT

Random Bundle		LARGE RECTANGLE 254x 380 x 70mm 10 x 15 x 2 ¾" 32 units/Bundle 1.01 Sq.Ft./Stone		SQUARE 254 x 254 x 70mm 10 x 10 x 2 ¾" 56 units/Bundle .67 Sq.Ft./Stone		RECTANGLE 127 x 254 x 70mm 5 x 10 x 2 ¾" 72 units/Bundle .34 Sq.Ft./Stone	Single 5x10 Unit		5x10 RECTANGLE 127 x 254 x 70mm 5 x 10 x 2 ¾" 280 units/Bundle .34 Sq.Ft./Stone
----------------------	---	---	---	--	---	--	-------------------------	---	--

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Standard
Joint Spacing - 2mm

TECHNOLOGIES

CLASSIC™
Budget-friendly traditional product mix

ANTIQUED

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits



ALMOND GROVE



LIMESTONE



SIERRA

Single Unit



STANDARD
300 x 100 x 200mm
11 7/8 x 3 7/8 x 7 7/8"
108 units/Bundle
.33 Fc.Ft./Stone

	STANDARD CLASSIC ANTIQUED
Bundle Type	SINGLE
Plant Produced	UXBRIDGE
Thickness (mm)	100 MM

FCFT PER	Bundle	-
	Layer	6.00
	Stone	0.33

PER BUNDLE	Layers	-
	Sections	3.00

LNFT PER	Bundle	-
	Unit	1.00

UNITS PER	SqFt	3.00
	Section	36.00
	Bundle	108.00

LBS PER	Layer	-
	Section	1,091
	Bundle	3,274

COLORS	Reflectance	Stock
Almond Grove	SR n/a SRI n/a	✓
Limestone	SR n/a SRI n/a	✓
Sierra	SR n/a SRI n/a	✓

SUNSET FIREPIT KITS



ROUND



SQUARE

See page 77 for more information.

Notes: Maximum height is 24" (under optimum conditions). *Based on 12" deep wall coverage = 21.4 sqft per bundle. Based on an 8" deep wall coverage = 32 sqft per bundle. All measurements are nominal. Contact Unilock for more information.



	CORNER SPLIT	XL WALL SPLIT	COPING 24"	WEDGE CAP
Bundle Type	RANDOM	SINGLE	SINGLE	SINGLE
Plant Produced	UXBRIDGE	UXBRIDGE	UXBRIDGE	UXBRIDGE
Thickness (mm)	150 MM	150 MM	75 MM	86 MM

FCFT PER	Bundle	15.00	21.33	-	64.00
	Layer	5.00	5.33	-	8.00
	Stone	0.83	0.67	1.94	0.67

PER BUNDLE	Layers	3.00	4.00	-	8.00
	Sections	-	-	2.00	-

LNFT PER	Bundle	-	-	64.00	-
	Unit	-	-	4.00	-

UNITS PER	SqFt	1.20	1.50	0.52	1.50
	Section	-	-	-	-
	Bundle	18.00	32.00	-	96.00

LBS PER	Layer	273	605	290	318
	Section	-	-	-	-
	Bundle	820	2,455	2,320	2,544

COLORS	Reflectance	Stock	Stock	Stock	Stock
Almond Grove	SR n/a SRI n/a	✓	✓	✓	✓
Granite	SR n/a SRI n/a	✓	✓	✓	✓
Sierra	SR n/a SRI n/a	✓	✓	✓	✓

APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Split / Standard

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits



ALMOND GROVE



GRANITE



SIERRA

Single Units		CORNER SPLIT 200 x 150 x 300mm 7 7/8 x 5 7/8 x 11 7/8" 18 units/Bundle .63 Fc.Ft./Stone		XL WALL SPLIT 400 x 150 x 300mm 15 3/4 x 5 7/8 x 11 7/8" 32 units/Bundle .67 Fc.Ft./Stone		COPING 24" 600 x 75 x 300mm 23 5/8 x 3 x 11 7/8" XX units/Bundle 1.94 Fc.Ft./Stone		WEDGE CAP SPLIT 248 x 86 x 330mm 9 7/8 x 3 1/2 x 13" 96 units/Bundle .67 Sq.Ft./Stone
--------------	---	--	---	--	--	---	---	--

Notes: Maximum height without setback 36" (under optimum conditions). Maximum height with setback is 42" (under optimum conditions). Higher walls can be achieved using geogrid reinforcement. Tapered units will allow for a minimum 7ft. outside radius. Wedge cap radius = 7", contains 8 Closed-end units per bundle. Closed-end not sold separately. All Concord Wall™ is layered and shipped on refundable skid. Coping is sectioned. Closed-end step tread is available. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. Contact your local Unilock Representative for details. Retaining wall engineering software is also available free of charge at www.unilock.com.



	STANDARD	STANDARD 1/2	CORNER 45°	CORNER 90°
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	ONTARIO	ONTARIO	ONTARIO	ONTARIO
Thickness (mm)	300 MM	300 MM	300 MM	300 MM

FCFT PER	Bundle	6.02	3.00	7.04	7.04
	Layer	6.02	3.00	7.04	7.04
	Stone	6.02	3.00	7.04	7.04

PER BUNDLE	Layers	1.00	1.00	1.00	1.00
	Sections	-	-	-	-

LNFT PER	Bundle	6.02	3.00	-	-
	Unit	6.02	3.00	-	-

UNITS PER	SqFt	0.17	0.33	0.14	0.14
	Section	-	-	-	-
	Bundle	1.00	1.00	1.00	1.00

LBS PER	Layer	1,680	800	1,480	1,320
	Section	-	-	-	-
	Bundle	1,680	800	1,480	1,320

COLORS	Reflectance	Stock	Stock	Stock	Stock
Natural	SR n/a SRI n/a	SO	SO	SO	SO

APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Standard

TECHNOLOGIES

CLASSIC™





Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C1372
Eligible for LEED v4.1 credits



NATURAL

Single Units				
	STANDARD	STANDARD 1/2	CORNER 45°	CORNER 90°
	1830 x 300 x 600mm	915 x 300 x 600mm	1520 x 300 x 600mm	1520 x 300 x 600mm
	72 x 11 7/8 x 23 5/8"	36 x 11 7/8 x 23 5/8"	59 7/8 x 11 7/8 x 23 5/8"	59 7/8 x 11 7/8 x 23 5/8"
	1 unit/Bundle 6.02 Fc.Ft./Stone	1 unit/Bundle 3.00 Fc.Ft./Stone	1 unit/Bundle 7.04 Fc.Ft./Stone	1 unit/Bundle 7.04 Fc.Ft./Stone

Notes: *Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY. Closed-end coping units are closed on both ends so that they may be used as left or right units. Tie-back units are reinforced with steel. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Standard

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C1372
Eligible for LEED v4.1 credits

	TIE-BACK	COPING HALF	COPING STANDARD	COPING CLOSED-END
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	ONTARIO	ONTARIO	ONTARIO	ONTARIO
Thickness (mm)	300 MM	300 MM	300 MM	300 MM

FCFT PER	Bundle	2.00	2.95	6.02	6.02
	Layer	2.00	2.95	6.02	6.02
	Stone	2.00	2.95	6.02	6.02

PER BUNDLE	Layers	1.00	1.00	1.00	1.00
	Sections	-	-	-	-

LNFT PER	Bundle	-	-	-	-
	Unit	-	-	-	-





UNITS PER	SqFt	0.50	0.34	0.17	0.17
	Section	-	-	-	-
	Bundle	1.00	1.00	1.00	1.00

LBS PER	Layer	1,660	780	1,560	1,560
	Section	-	-	-	-
	Bundle	1,660	780	1,560	1,560

COLORS	Reflectance	Stock	Stock	Stock	Stock
Natural	SR n/a SRI n/a	SO	SO	SO	SO



NATURAL

Single Units				
	TIE-BACK	COPING 1/2	COPING STANDARD	COPING CLOSED-END
	1830 x 300 x 600mm 72 x 11 7/8 x 23 5/8"	915 x 300 x 600mm 36 x 11 7/8 x 23 5/8"	1830 x 300 x 600mm 72 x 11 7/8 x 23 5/8"	1830 x 300 x 600mm 72 x 11 7/8 x 23 5/8"
	1 unit/Bundle	1 unit/Bundle	1 unit/Bundle	1 unit/Bundle
	6.02 Fc.Ft./Stone	2.95 Fc.Ft./Stone	6.02 Fc.Ft./Stone	6.02 Fc.Ft./Stone

Notes: *Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY. Closed-end coping units are closed on both ends so that they may be used as left or right units. Tie-back units are reinforced with steel. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.



	TIE-BACK	CORNER 90°	STANDARD	COPING	COPING CLOSED-END
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	ONTARIO	ONTARIO	ONTARIO	ONTARIO	ONTARIO
Thickness (mm)	300 MM	300 MM	300 MM	300 MM	300 MM

FCFT PER	Bundle	1.17	16.67	24.10	24.10	6.02
	Layer	1.17	4.17	6.02	6.02	6.02
	Stone	1.17	4.17	6.02	6.02	6.02

PER BUNDLE	Layers	2.00	2.00	2.00	2.00	2.00
	Sections	-	-	-	-	-

LNFT PER	Bundle	-	-	24.10	24.10	24.10
	Unit	-	-	6.02	6.02	6.02

UNITS PER	SqFt	0.85	0.24	0.17	0.17	0.17
	Section	-	-	-	-	-
	Bundle	1.00	-	1.00	1.00	1.00

LBS PER	Layer	940	460	884	884	884
	Section	-	-	-	-	-
	Bundle	940	-	884	884	884

COLORS	Reflectance	Stock	Stock	Stock	Stock	Stock
Natural	SR n/a SRI n/a	SO	SO	SO	SO	SO

APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Standard

TECHNOLOGIES

CLASSIC™






Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C1372
Eligible for LEED v4.1 credits



NATURAL

Single Units					
	TIE-BACK 1830 x 300 x 360mm 72 x 11 7/8 x 14 1/4" 1 unit/Bundle 1.17 Fc.Ft./Stone	CORNER 900 x 300 x 360mm 36 x 11 7/8 x 14 1/4" 1 unit/Bundle 4.17 Fc.Ft./Stone	STANDARD 1830x 300 x 360mm 72 x 11 7/8 x 14 1/4" 1 unit/Bundle 6.02 Fc.Ft./Stone	COPING 1830x 300 x 360mm 72 x 11 7/8 x 14 1/4" 1 unit/Bundle 6.02 Fc.Ft./Stone	COPING CLOSED-END 1830x 300 x 360mm 72 x 11 7/8 x 14 1/4" 1 unit/Bundle 6.02 Fc.Ft./Stone

Notes: *Special Order - Lead time is required, minimum quantities apply. SOLD IN FULL BUNDLES ONLY. Closed-end coping units are closed on both ends so that they may be used as left or right units. Tie-back units are reinforced with steel. 1/2 Standard units are slightly tapered and can be used to create a 45 foot radius. Refer to terms and conditions for placement rates. Unilock, through Risi Stone® Systems International, can provide preliminary site engineering for most commercial projects. Soils information, site drawings, and loading requirements are some of the information details required in order to provide this preliminary site engineering. All measurements are nominal. Contact Unilock for more information.




The enhanced Estate Wall System with 6" and 3" high units, is ideal for all residential landscape walls and vertical element construction. The front and back of each unit is rock-faced making it perfect for seat walls and the unique tapered units can be used for both straight or curved applications.

Estate Wall™ System

Units



WALL UNITS



COPING




CORNER UNITS



NOTE: See Product Data for packaging information.



NOTE: Different products can be used for Estate Wall coping. LedgeStone and Fullnose Edger are two of the most popular.

UNIVERSAL BASE UNIT



NOTE: Unilock Recommends using the Universal Base Units

Cross Sections




*Higher wall up to 6' can be achieved using geogrid reinforcement. Contact your Unilock Territory Manager.

MAXIMUM HEIGHT FOR VERTICAL APPLICATION - 21"
MAXIMUM HEIGHT FOR SETBACK APPLICATION - 33"

Corners


CONVERTIBLE LARGE WEDGE UNITS



To split a large convertible unit, use a hammer and chisel to score the top and sides, then flip the unit upside down and use the chisel to break the unit. This may require a couple of hits along the groove to achieve a clean break.

Each bundle contains approximately 9 convertible units.


90° SEAT WALL CORNER



LOCKING INSERTS




Depending on the application or the wall strength required, you can construct the Estate Wall System vertically or with a setback. To assist in alignment and locking, proprietary plastic inserts are provided with each bundle. Depending on the orientation of the insert will dictate whether it goes up vertical or with a setback.

Note: It is strongly recommended that you use adhesive on all rows and for all applications to achieve maximum stability and strength.



Seat Walls



SEAT WALL TERMINATION



Alternate courses



System Patterns

RANDOM PATTERNS OPEN BACK WALL



Use Universal Base Units for base

RANDOM PATTERNS SOLID WALL




Use Universal Base Units for base

CURVED RADIUS

Radius achieved using only the tapered (wedge) units.

Radius in inches	35"	27"	35"	44"	31"	35"	40"
Unit sequence	9", 12", 14 ³ / ₄ "	Only 9" Units	Only 12" Units	Only 14 ³ / ₄ " Units	9", 12", 9", 12"	9", 14 ³ / ₄ ", 9"	12", 14 ³ / ₄ ", 12", 14 ³ / ₄ "
Note:	Uses all units in bundle	These sequences will have left over units. Plan to use left overs in other parts of the project.					

Random Units



Although the three tapered unit sizes come packaged together, they can be separated to achieve various radius projects. If you construct a radius using only one size unit, the other units will be left over. Careful planning will allow you to use these units elsewhere.



	TAPERED SPLIT	CORNER SPLIT	TAPERED SPLIT	CORNER SPLIT	COPING TAPERED SPLIT
Bundle Type	RANDOM	SINGLE	RANDOM	SINGLE	RANDOM
Plant Produced	UXBRIDGE	UXBRIDGE	UXBRIDGE	UXBRIDGE	UXBRIDGE
Thickness (mm)	75 MM	75 MM	150 MM	150 MM	75 MM

FCFT PER	Bundle	24.00	16.38	24.00	16.38	14.70
	Layer	3.00	2.05	6.00	4.10	2.10
	Stone	0.25	0.26	0.50	0.51	0.23

PER BUNDLE	Layers	8.00	8.00	4.00	4.00	7.00
	Sections	-	-	-	-	-

LNFT PER	Bundle	-	-	-	-	56.87
	Unit	-	-	-	-	0.90

UNITS PER	SqFt	4.00	3.91	2.00	1.95	4.29
	Section	-	-	-	-	-
	Bundle	96.00	64.00	48.00	32.00	63.00

LBS PER	Layer	271.00	264	585	444	294
	Section	-	-	-	-	-
	Bundle	2,164	2,110	2,340	1,776	2,060

COLORS	Reflectance	STOCK	STOCK	STOCK	STOCK	STOCK
Almond Grove	SR.n/a SRI n/a	✓	✓	✓	✓	✓
Charcoal	SR.n/a SRI n/a					✓
Granite	SR.n/a SRI n/a	✓	✓	✓	✓	✓
Sierra	SR.n/a SRI n/a	✓	✓	✓	✓	✓

APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: contractor.unilock.com

APPEARANCE

Edge Detail - n/a

Surface Texture - Split

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits



ALMOND GROVE



CHARCOAL



GRANITE



SIERRA

Random Bundle				Single Unit		Coping Bundle				
	LARGE TAPERED 400 x 150 x 228mm 15 3/4 x 5 7/8 x 9" 16 units/Bundle .50 Fc.Ft./Stone	MEDIUM TAPERED 300 x 150 x 228mm 11 7/8 x 5 7/8 x 9" 16 units/Bundle .50 Fc.Ft./Stone	SMALL TAPERED 200 x 150 x 228mm 7 7/8 x 5 7/8 x 9" 16 units/Bundle .50 Fc.Ft./Stone		CORNER SPLIT 320 x 150 x 230mm 12 5/8 x 5 7/8 x 9" 32 units/Bundle .51 Sq.Ft./Stone		COPING TAPERED 280 x 75 x 300mm 11 x 3 x 11 7/8" 63 units/Bundle .23 Sq.Ft./Stone			
	Random Bundle						Single Unit		Coping Bundle	
		LARGE TAPERED 375 x 75 x 228mm 14 7/8 x 3 x 9" 32 units/Bundle .25 Fc.Ft./Stone	MEDIUM TAPERED 300 x 75 x 228mm 11 7/8 x 3 x 9" 32 units/Bundle .25 Fc.Ft./Stone		SMALL TAPERED 200 x 75 x 228mm 7 7/8 x 3 x 9" 32 units/Bundle .25 Fc.Ft./Stone			CORNER SPLIT 320 x 75 x 230mm 12 5/8 x 3 x 9" 64 units/Bundle .23 Sq.Ft./Stone		

Notes: Random wall bundles have convertible large units that can be used for corners or ending seat walls. End caps not sold separately. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Standard
Joint Spacing - n/a

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

	RANDOM CLASSIC	PILLAR CLASSIC
Bundle Type	RANDOM	SINGLE
Plant Produced	UXBRIDGE	UXBRIDGE
Thickness (mm)	100 MM	100 MM

FCFT PER	Bundle	29.92	32.00
	Layer	9.97	-
	Stone	0.50	-

PER BUNDLE	Layers	3.00	3.00
	Sections	-	-

LNFT PER	Bundle	89.06	96.00
	Unit	1.48	1.33

UNITS PER	SqFt	2.01	1.49
	Section	-	-
	Bundle	60.00	72.00

LBS PER	Layer	881	936
	Section	-	-
	Bundle	2,643	2,808

COLORS	Reflectance	Stock	Stock
Almond Grove	SR.n/a SRI n/a	✓	✓
Limestone	SR.n/a SRI n/a	✓	✓
Sierra	SR.n/a SRI n/a	✓	✓



ALMOND GROVE



LIMESTONE




SIERRA

Random Bundle	LARGE RECTANGLE	RECTANGLE	SMALL RECTANGLE	XL RECTANGLE	Single Unit	CORNER/PILLAR
	500 x 100 x 200mm 19 ¾ x 3 7/8 x 7 7/8 15 units/Bundle	400 x 100 x 200mm 15 ¾ x 3 7/8 x 7 7/8 15 units/Bundle	300 x 100 x 200mm 11 7/8 x 3 7/8 x 7 7/8 15 units/Bundle	600 x 100 x 200mm 23 5/8 x 3 7/8 x 7 7/8 15 units/Bundle		400 x 100 x 200mm 15 ¾ x 3 7/8 x 7 7/8 72 units/Bundle


Notes: Sold in full bundles only and is produced and sold on a required, refundable skid. Spacing strips are shipped with random wall bundles to create even spacing between units. LedgeStone®, Unilock Natural Stone or 6"x12" Fullnose complement as possible coping options. All measurements are nominal. Contact Unilock for more information.

Lineo™ Dimensional Stone

Shadow Box - Spacers (supplied with bundle of product)





"T" Spacers
1" x 4 3/16" x 2"



"Strip" Spacers
3/16" x 3/8" x 22"

Adhesive "mound" is placed every 4 inches apart.

Mound must be minimum 3/8" high so that the top and bottom are securely adhered.



Notes:

Lineo is not a retaining wall. Lineo is a decorative landscape wall, with a typical height of 12" - 16" above grade. (Higher walls are possible when engineered by a professional engineer.)

In many cases, experienced installers are able to construct higher walls based on the actual design of the project or landscape feature. For example, designs containing 90 degree corners, box-like planters, hollow pillars and landscape features such as grill islands, can be successfully constructed to higher heights.

Disclaimer: The strength and capacity of a Lineo installation is dependent on many factors such as base material, site conditions, drainage, surcharge, design, and the quality and quantity of concrete adhesive used. Unilock cannot be responsible for installation failures. The performance of a Lineo installation rests solely on the installer or project engineer.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products: contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Split

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
Eligible for LEED v4.1 credits

	CORNER SPLIT	333 SPLIT	500 SPLIT	925 SPLIT	COPING SPLIT	CLOSED-END COPING
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	UXBRIDGE	UXBRIDGE	UXBRIDGE	UXBRIDGE	UXBRIDGE	GORMLEY
Thickness (mm)	185 MM	185 MM	185 MM	185 MM	185 MM	185 MM

FCFT PER	Bundle	17.19	18.00	12.00	6.00	12.00	14.43
	Layer	5.73	6.00	4.00	2.00	4.00	4.81
	Stone	2.87	2.00	2.00	2.00	2.00	2.41

PER BUNDLE	Layers	3.00	3.00	3.00	3.00	3.00	3.00
	Sections	-	-	-	-	-	-

LNFT PER	Bundle	-	-	19.50	9.75	19.50	23.70
	Unit	-	-	3.25	3.25	3.25	3.95

UNITS PER	SqFt	0.35	0.50	0.50	0.50	0.50	0.42
	Section	-	-	-	-	-	-
	Bundle	6.00	9.00	6.00	3.00	6.00	6.00

LBS PER	Layer	954	954	954	954	927	1,140
	Section	-	-	-	-	-	-
	Bundle	2,862	2,862	2,862	2,862	2,780	3,420

COLORS	Reflectance	Stock	Stock	Stock	Stock	Stock	Stock
Granite	SR.n/a SRI n/a	SO	SO	SO	SO	✓	✓
Natural	SR.n/a SRI n/a	SO					



GRANITE



NATURAL

Single Units	CORNER SPLIT	STANDARD 333 SPLIT	STANDARD 500 SPLIT	STANDARD 925 SPLIT	COPING SPLIT	C-E COPING
	925 x 185 x 500mm 36 1/2 x 7 3/8 x 19 3/4" 6 units/Bundle 2.87 Fc.Ft./Stone	1000 x 185 x 333mm 39 3/8 x 7 3/8 x 13" 9 units/Bundle 2.00 Fc.Ft./Stone	1000 x 185 x 500mm 39 3/8 x 7 3/8 x 19 3/4" 6 units/Bundle 2.00 Fc.Ft./Stone	1000 x 185 x 925mm 39 3/8 x 7 3/8 x 36 1/2" 3 units/Bundle 2.00 Fc.Ft./Stone	1000 x 185 x 500mm 39 3/8 x 7 3/8 x 19 3/4" 6 units/Bundle 2.00 Fc.Ft./Stone	Granite Only 1200 x 185 x 500mm 47 1/4 x 7 3/8 x 19 3/4" 6 units/Bundle 2.41 Fc.Ft./Stone

Notes: **Special Order - Lead time is required, minimum quantities apply.** Product is sold on a required, refundable skid. Coping units can be used to construct steps. Retaining wall engineering software is also available free of charge at www.unilock.com. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor website under Products:

contractor.unilock.com

APPEARANCE

Edge Detail - n/a

Surface Texture - Smooth

Joint Spacing - n/a

TECHNOLOGIES

CLASSIC™

Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits credits



LIMESTONE

	STANDARD SMOOTH	COPING SMOOTH
Bundle Type	SINGLE	SINGLE
Plant Produced	CHICAGO	CHICAGO
Thickness (mm)	180 MM	180 MM

FCFT PER	Bundle	23.25	23.25
	Layer	7.75	7.75
	Stone	1.94	1.94

PER BUNDLE	Layers	3.00	3.00
	Sections	-	-

LNFT PER	Bundle	39.37	39.37
	Unit	3.28	3.28

UNITS PER	SqFt	0.52	0.52
	Section	-	-
	Bundle	12.00	12.00

LBS PER	Layer	1,029	1,029
	Section	-	-
	Bundle	3,086	3,086

COLORS	Reflectance	Stock	Stock
Limestone	SR.n/a SRI n/a	✓	✓

Single Units



STANDARD CORNER
1000 x 180 x 290mm
39 3/8 x 7 x 11 1/2"
12 units/Bundle
.25 Fc.Ft./Stone




COPING
1000 x 180 x 290mm
39 3/8 x 7 x 11 1/2"
12 units/Bundle
.33 Fc.Ft./Stone

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. Coping units can be used to construct steps. Retaining wall engineering software is also available free of charge at www.unilock.com. All measurements are nominal. Contact Unilock for more information.

U-Cara® Multi-Face Wall System



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Smooth, Standard, Series Exposed, Umbriano Mottled, Pitched & Flamed

TECHNOLOGIES

ENDURACOLOR™

Refined surface and long-lasting color

COLORFUSION™ (UMBRIANO)

Subtly mottled colored finish



TECHNICAL INFORMATION

Conforms to ASTM C1372

Eligible for LEED v4.1 credits



Download the U-Cara Multi-Face Wall System Installation Guide.



3" PANEL

U-Cara® Multi-Face Wall System

	Standard 6" Fascia Panel Smooth	Closed-End Fascia Panel Smooth	Standard 3" Fascia Panel Series Exposed	Standard 6" Fascia Panel Umbriano	Closed-End Fascia Panel Umbriano	Standard 6" Fascia Panel Pitched	Closed-End Fascia Panel Pitched
Bundle Type	SINGLE	RANDOM	SINGLE	SINGLE	RANDOM	SINGLE	RANDOM
Plant Produced	NEW YORK	NEW YORK	CHICAGO	NEW YORK	NEW YORK	NEW YORK	NEW YORK
Thickness (mm)	150 MM	150 MM	71 MM	150 MM	150 MM	150 MM	150 MM

FCFT PER	Bundle	61.52	45.15	59.32	61.49	45.15	61.52	45.15
	Layer	10.25	9.03	9.89	10.25	9.03	10.25	9.03
	Stone	0.73	1.29	0.18	0.73	1.29	0.73	1.29

PER BUNDLE	Layers	6.00	5.00	6.00	6.00	5.00	6.00	5.00
	Sections	-	-	-	-	-	-	-

LNFT PER	Bundle	129.50	74.95	-	-	89.95	129.50	89.95
	Unit	1.54	2.14	-	-	2.57	1.54	2.57

UNITS PER	SqFt	1.37	0.78	5.66	1.37	0.78	1.37	0.78
	Section	-	-	-	-	-	-	-
	Bundle	84.00	35.00	336.00	84.00	35.00	84.00	35.00

LBS PER	Layer	274	207	250	274	207	291	236
	Section	-	-	-	-	-	-	-
	Bundle	1,647	1,033	1,501	1,647	1,033	1,745	1,179

COLORS	Reflectance	Stock	Stock	Stock	Stock	Stock	Stock
Natural	SR.n/a sRI n/a	✓	✓				
Fossil	SR.n/a sRI n/a	✓	✓			✓	✓
French Grey	SR.n/a sRI n/a				SO	SO	
Steel Mountain	SR.n/a sRI n/a	✓	✓			✓	✓
Summer Wheat	SR.n/a sRI n/a				SO	SO	
Onyx Black	SR.n/a sRI n/a			✓			
Opal Blend	SR.n/a sRI n/a	✓	✓				
Winter Marvel	SR.n/a sRI n/a				SO	SO	

Fascia Panels		6" STANDARD FASCIA PANEL 150 x 466 x 60mm 5 7/8 x 18 3/8 x 2 3/8" 84 units/Bundle .73 Sq.Ft./Stone		3" FASCIA PANEL 71 x 231 x 60mm 2 7/8 x 9 x 2 3/8" 336 units/Bundle .18 Sq.Ft./Stone
	2 Unit Corner		STANDARD FASCIA HALF PANEL 150 x 233 x 60mm 5 7/8 x 9 1/4 x 2 3/8" 35 units/Bundle 1.29 Sq.Ft./Stone	

Notes: Lead time is required, minimum quantities apply. Sold in full bundles. Produced and sold on a required refundable skids. Opal Corner Bundle Only - 54.2 Face Feet/Bundle; contact Customer Service for details.

U-Cara® Multi-Face Wall System



APPLICATIONS



ENDURACOLOR™

Refined surface and long-lasting color

COLORFUSION™

Subtly mottled colored finish

TECHNICAL INFORMATION

Conforms to ASTM C 1262
Eligible for LEED v4.1 credits

CROSS SECTIONS


All Cross Sections are available on Unilock's Contractor website under Products:

contractor.unilock.com

APPEARANCE

Edge Detail - n/a
Surface Texture - Smooth, Standard, Series™ Exposed, Umbriano® Mottled, Pitched & Flamed

U-CARA RETAINING WALL GEOGRID SECTION



Umbriano® Panel



WINTER MARVEL



FRENCH GREY




SUMMER WHEAT

U-CARA®

CROSS SECTION

REF: Detail_U-Cara_Garden_Wall

Garden Wall - Max Height 15'




Notes: This cross section is intended for preliminary design purposes only. Confirm site conditions and consult with a qualified design professional or installer prior to installation.

U-CARA®

CROSS SECTION

REF: Detail_U-Cara_Seal_Wall

Seat Wall - Max Height 21'



Notes: This cross section is intended for preliminary design purposes only. Confirm site conditions and consult with a qualified design professional or installer prior to installation.

U-Cara® Multi-Face Wall System

Components



SURE TRACK CORNER BACKER
175 x 150 x 294mm
6⁷/₈ x 5⁷/₈ x 11⁵/₈"



SURE TRACK LARGE BACKER
150 x 200 x 294mm
7⁷/₈ x 5⁷/₈ x 11⁵/₈"



SURE TRACK STANDARD BACKER
190 x 150 x 150mm
7¹/₂ x 5⁷/₈ x 5⁷/₈"

	LARGE/CORNER/ PILLAR BACKER	LARGE BACKER	STANDARD BACKER
Bundle Type	SINGLE	SINGLE	SINGLE
Plant Produced	UXBRIDGE	UXBRIDGE	UXBRIDGE
Thickness (mm)	150 MM	150 MM	150 MM

FCFT PER	Bundle	15.82	20.35	32.21
	Layer	3.96	6.78	10.74
	Stone	0.28	0.32	0.31

PER BUNDLE	Layers	4.00	3.00	3.00
	Sections	-	-	-

LNFT PER	Bundle	-	41.34	65.46
	Unit	-	0.66	0.62

UNITS PER	SqFt	3.54	3.10	3.26
	Section	-	21.00	35.00
	Bundle	56.00	63.00	105.00

LBS PER	Layer	503	878	772
	Section	-	-	-
	Bundle	2,012	2,635	2,315

Series 3" Panel



ONYX BLACK

Smooth Panel



FOSSIL



STEEL MOUNTAIN




OPAL BLEND

Pitched Panel



FOSSIL



STEEL MOUNTAIN

Recommended Base Unit



UNIVERSAL BASE UNIT
14 x 19 x 2"
355 x 482 x 55mm

Extra Components




SURE TRACK CORNER INSERT
L = 2"
50mm

Notes: Product is shipped on a required, refundable skid. All measurements are nominal. Contact Unilock for more information.

U-Cara® Modular System

The U-Cara Modular System offers a variety of aluminum frames that can be mixed and matched to construct vertical features like grill islands. Speak to your contractor to select a design and a U-Cara fascia panel finish to suit your project.

With the U-Cara Modular System you can build Grill Islands, Bars, Back splashes, Fire Places and Pillars.



NO.	MODEL	DESCRIPTION
RS-UCARA000001	URS	UCARA 8" RAIL (10/PACK)
RS-UCARA000002	URS	ALIGNMENT BARS 39" (10/PACK)
RS-UCARA001000	UL-GC	UNIVERSAL GRILL CABINET
RS-UCARA002000	UL-BC	BASE CABINET
RS-UCARA003000	UL-CC	CORNER CABINET 27.5" x 27.5"
RS-UCARA003001	UL-CCOS	CORNER CABINET 27.5" x 36.5" OS
RS-UCARA003002	UL-CCBP	CORNER CABINET BACK PANEL
RS-UCARA004000	UL-ECK	END CLAD KIT 23.5"
RS-UCARA004001	UL-ECKOS	END CLAD KIT 36.5" OS
RS-UCARA005000	UL-BS	BACKSPLASH-GRILL/BASE UNIT
RS-UCARA005001	UL-BSCC	BACKSPLASH CORNER CABINET
RS-UCARA005002	UL-BSCCOS	BACKSPLASH CORNER CABINET OS
RS-UCARA006000	UL-DD	STAINLESS DOUBLE ACCESS DOORS 27"
RL-UCARA007000	UL-PU	PILLAR UNIT



Download the U-Cara Modular Fireplace Installation Guide.

U-Cara® Wall Mount System



The U-Cara Wall Mount System allows you to put the finishing touches on your project by cladding existing structures like unsightly exposed foundation areas or concrete steps with U-Cara fascia panels.




U-CARA ALIGNMENT BAR:
39" LENGTH - SOLD IN PACKS OF 10 PIECES

U-CARA RAILS:
8' LENGTH - SOLD IN PACKS OF 10 PIECES

Fireplace WOOD BURNING

This truly revolutionary U-Cara Modular Fireplace is easily constructed in one day with only a handful of basic tools. The ability to mix and match several panel color and/or textures allows you to be creative while maintaining the theme of the project overall.



NOTE:

Complete assembly instructions can be downloaded from unilock.com

Always observe local building codes.

Fireplace GAS

Gas Fireplaces make a wonderful addition to any urban landscape especially where access is limited and/or where wood burning is prohibited.

Construct one-sided or two-sided fireplaces in a matter of hours.

NOTE:

Complete assembly instructions can be downloaded from unilock.com

Always observe local building codes.



Architectural Pillar Cap



APPLICATIONS



APPEARANCE

Edge Detail - n/a
 Surface Texture - Smooth
 Joint Spacing - 3mm

TECHNOLOGIES

ENDURACOLOR™
 Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

	PILLAR CAP 28" SMOOTH ENDURACOLOR	
Bundle Type	SINGLE	
Plant Produced	NEW YORK	
Thickness (mm)	100 MM	

SQFT PER	Bundle	3.06
	Layer	0.77
	Stone	0.77

PER BUNDLE	Layers	4.00
	Sections	-

LNFT PER	Bundle	9.36
	Unit	2.34

UNITS PER	SqFt	1.31
	Section	-
	Bundle	4.00

LBS PER	Layer	234
	Section	-
	Bundle	935

COLORS	Reflectance	Stock
Light Grey	SR n/a SRI n/a	✓
Midnight Charcoal	SR n/a SRI n/a	✓



LIGHT GREY



MIDNIGHT CHARCOAL

Single Unit



PILLAR CAP
 711 x 100mm x 711mm
 28 x 3 7/8 x 28"
 4 unit/Bundle
 .77 Fc.Ft./Stone

Notes: Product is shipped on a required, refundable skid. All measurements are nominal. Contact Unilock for more information.

Fullnose™ Edger

CLASSIC



APPLICATIONS



APPEARANCE

Edge Detail - Zero
 Surface Texture - Smooth
 Joint Spacing - 2mm

TECHNOLOGIES

CLASSIC™
 Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 936
 Eligible for LEED v4.1 credits

	FULLNOSE EDGER CLASSIC SMOOTH
Bundle Type	SINGLE
Plant Produced	UXBRIDGE
Thickness (mm)	70 MM

FCFT PER	Bundle	-
	Layer	-
	Stone	-

PER BUNDLE	Layers	4.00
	Sections	-

LNFT PER	Bundle	96.00
	Unit	0.50


UNITS PER	SqFt	-
	Layer	48.00
	Bundle	192.00

LBS PER	Layer	704
	Section	-
	Bundle	2815

COLORS	Reflectance	Stock
Almond Grove	SR. n/a SRI n/a	✓
Charcoal	SR. n/a SRI n/a	✓
Limestone	SR. n/a SRI n/a	✓



ALMOND GROVE



CHARCOAL



LIMESTONE

Single Unit



FULLNOSE EDGER
 150 x 300 x 70mm
 5 7/8 x 11 7/8 x 2 3/4"
 192 unit/Bundle

Notes: Units can be adhered to pool edge using Unilock Concrete Adhesive, or with mortar. Always observe proper construction techniques when adhering pavers to a surface. Consult your local pool contractors for installation specifics.



APPLICATIONS



APPEARANCE

Edge Detail - n/a
Surface Texture - Textured

TECHNOLOGIES

REALA™

Cast from natural stone

TECHNICAL INFORMATION

Conforms to ASTM C 1776
Eligible for LEED v4.1 credits

	FULLNOSE COPING	STANDARD COPING	STANDARD CLOSED-END	LARGE COPING	LARGE CLOSED-END
Bundle Type	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Plant Produced	CHICAGO	CHICAGO	CHICAGO	CHICAGO	CHICAGO
Thickness (mm)	60 MM	70 MM	70 MM	70 MM	70 MM

FCFT PER	Bundle	5.12	5.52	5.52	6.87	6.87
	Layer	-	-	-	-	-
	Stone	0.39	0.46	0.46	0.57	0.57

PER BUNDLE	Layers	-	-	-	-	-
	Sections	13.00	12.00	12.00	12.00	12.00

LNFT PER	Bundle	26.00	24.00	24.00	30.00	30.00
	Unit	2.00	2.00	2.00	2.50	2.50

UNITS PER	SqFt	2.54	2.18	2.18	1.75	1.75
	Section	1.00	1.00	1.00	1.00	1.00
	Bundle	13.00	12.00	12.00	12.00	12.00

LBS PER	Layer	-	-	-	-	-
	Section	167	64	66	94	93
	Bundle	2,169	772	796	1,128	1,116

COLORS	Reflectance	Stock	Stock	Stock	Stock	Stock
Buff	SR.n/a SRI n/a	✓	✓	✓	✓	✓
Grey	SR.n/a SRI n/a	✓	✓	✓	✓	✓



BUFF



GREY

Single Units	FULLNOSE COPING	STANDARD COPING	STANDARD CLOSED-END COPING	LARGE COPING	LARGE CLOSED-END COPING
	610 x 305 x 60mm 24 x 12 x 2 3/8" 13 unit/Bundle .39 Fc.Ft./Stone	610 x 305 x 70mm 24 x 12 x 2 3/4" 12 unit/Bundle .46 Fc.Ft./Stone	610 x 305 x 70mm 24 x 12 x 2 3/8" 12 unit/Bundle .46 Fc.Ft./Stone	762 x 343 x 70mm 30 x 13 1/2 x 2 3/4" 12 unit/Bundle .57 Fc.Ft./Stone	762 x 343 x 70mm 30 x 13 1/2 x 2 3/4" 12 unit/Bundle .57 Fc.Ft./Stone

Notes: This product is produced and sold on a required, refundable skid. Coping is rock faced on the front and the back; Closed-end coping and steps are rock faced on three sides. All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - n/a
Surface Texture - Textured

TECHNOLOGIES

REALA™
Cast from natural stone

TECHNICAL INFORMATION

Conforms to ASTM C 1776
Eligible for LEED v4.1 credits



BUFF



GREY

Single Units



24" PILLAR CAP
610 x 610 x 100mm
24 x 24 x 3 7/8"
5 unit/Bundle
.66 Fc.Ft./Stone

		24" PILLAR CAP
	Bundle Type	SINGLE
	Plant Produced	CHICAGO
	Thickness (mm)	100 MM

FCFT PER	Bundle	3.28
	Layer	0.66
	Stone	0.66

PER BUNDLE	Layers	5.00
	Sections	-

LNFT PER	Bundle	10.04
	Unit	2.01

UNITS PER	SqFt	1.52
	Section	-
	Bundle	5.00

LBS PER	Layer	159
	Section	-
	Bundle	795

COLORS	Reflectance	Stock
Buff	SR.n/a SRI n/a	✓
Grey	SR.n/a SRI n/a	✓

Universal Coping & Base

ENDURACOLOR™ / CLASSIC



APPLICATIONS



APPEARANCE

Edge Detail - n/a

Surface Texture - Standard / Smooth

TECHNOLOGIES

CLASSIC™ (BASE)

Budget-friendly traditional product mix

ENDURACOLOR™ (COPING)

Refined surface and long-lasting color

TECHNICAL INFORMATION

Conforms to ASTM C 1372

Eligible for LEED v4.1 credits

	UNIVERSAL BASE CLASSIC	UNIVERSAL COPING SMOOTH ENDURACOLOR
Bundle Type	SINGLE	SINGLE
Plant Produced	UXBRIDGE	NEW YORK
Thickness (mm)	55 MM	70 MM

FCFT PER	Bundle	-	17.44
	Layer	-	2.18
	Stone	-	0.36

PER BUNDLE	Layers	9.00	8.00
	Sections	-	-

LNFT PER	Bundle	63.00	75.90
	Unit	1.17	1.58

UNITS PER	SqFt	-	2.75
	Section	-	-
	Bundle	54.00	48.00

LBS PER	Layer	278	358
	Section	-	-
	Bundle	2,502	2,864

COLORS	Reflectance	Stock	Stock
Light Grey	SR.n/a SRI n/a		✓
Midnight Charcoal	SR.n/a SRI n/a		✓
Natural	SR.n/a SRI n/a	✓	



LIGHT GREY



MIDNIGHT CHARCOAL



NATURAL

Single Units



UNIVERSAL COPING

482 x 70 x 355mm
19 x 2 ¾ x 14"
48 units/Bundle
.36 Fc.Ft./Stone



UNIVERSAL BASE

482 x 55 x 355mm
19 x 2 ¼ x 14"
54 units/Bundle

Notes: **SOLD IN FULL BUNDLES ONLY** and is shipped on a required, refundable skid. Two (2) End Coping units per Layer (1 Left & 1 Right). All measurements are nominal. Contact Unilock for more information.

Sunset Fire Pit Kit

CLASSIC



APPLICATIONS



APPEARANCE

Edge Detail - Zero
 Surface Texture - Standard
 Joint Spacing - n/a
 Void % - n/a

TECHNOLOGIES

CLASSIC™
 Budget-friendly traditional product mix

ANTIQUED™

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372
 Eligible for LEED v4.1 credits

	SUNSET SQUARE W / INSERT	SUNSET ROUND W / INSERT
Bundle Type	SINGLE	SINGLE
Dimension Metric	1100 x 1100 x 400mm	1300 x 1300 x 400mm
Dimension Imperial	43 3/8 x 43 3/8 x 15 3/4"	51 1/4 x 51 1/4 x 15 3/4"
Thickness (mm)		300 MM

DIAMETER (inch)	Outside	43	52
	Inside	29	36
	Insert	27	35

LAYER PER UNIT	4	4
UNIT PER LAYER	12	18
UNIT PER PALLET	48	72

LBS PER PALLET	1,357	1,499
-----------------------	-------	-------

COLORS	Reflectance	Stock	Stock
Almond Grove	SR. n/a SRI n/a	✓	✓
Limestone	SR. n/a SRI n/a	✓	✓
Sierra	SR. n/a SRI n/a	✓	✓



ALMOND GROVE



LIMESTONE



SIERRA

The following accessories are available for any fire pit kit.
 Contact your local Territory Manager for details.



ROUND FIRE SCREEN
 (works with Sunset Round only)




24" SWING AWAY GRILL



KETTLE HOOK



ACCESSORY POST
 WITH COLLAR



UNILOCK REDUCED SMOKE INSERT

SELECTED FIRE PIT AVAILABLE WITH ZENTRO TECHNOLOGY FIRE PIT INSERT

There's nothing like relaxing around a firepit to bring family and friends closer together. But with ordinary firepits, smoke always blows in someone's face - usually yours. With Unilock Reduced Smoke Inserts, stinging eyes are a thing of the past. Zentro's patent-pending technology reburns smoke before it gets anywhere near your eyes. Say hello to good times and good-bye to smoke.

Single Unit



SUNSET SQUARE W/INSERT
 1100 x 1100 x 300mm
 43 3/8 x 43 3/8 x 15 3/4"



SUNSET ROUND W/INSERT
 1300 x 1300 x 300mm
 51 1/4 x 51 1/4 x 15 3/4"

FIRE PIT WARNING

Wood-burning fire pits must be lined with a proper metal insert or refractory (fire-rated) brick to protect the concrete components from extreme exposure to heat. Extreme heat on a concrete surface may affect the structural integrity of the concrete and can be dangerous. The floor of the fire pit should always be constructed using refractory brick or a sand bed. For your safety, always use a spark screen over the fire.

Notes: All measurements are nominal. Contact Unilock for more information.



APPLICATIONS



APPEARANCE

Edge Detail - Zero
 Surface Texture - Standard
 Joint Spacing - n/a
 Void % - n/a

TECHNOLOGIES

CLASSIC™


Budget-friendly traditional product mix

ANTIQUED™

Distressed, timeworn finish

TECHNICAL INFORMATION

Conforms to ASTM C 1372
 Eligible for LEED v4.1 credits



UNILOCK REDUCED SMOKE INSERT

SELECTED FIRE PITS AVAILABLE WITH ZENTRO TECHNOLOGY FIRE PIT INSERT

There's nothing like relaxing around a firepit to bring family and friends closer together. But with ordinary firepits, smoke always blows in someone's face - usually yours. With Unilock Reduced Smoke Inserts, stinging eyes are a thing of the past. Zentro's patent-pending technology reburns smoke before it gets anywhere near your eyes. Say hello to good times and good-bye to smoke.

	ROMANSTACK ROUND W / INSERT
Bundle Type	SINGLE
Dimension Metric	1525 x 1525 x 400mm
Dimension Imperial	60 x 60 x 15 3/4"
Thickness (mm)	300 MM

DIAMETER (inch)	Outside	60
	Inside	44
	Insert	43

LAYER PER UNIT	4
UNIT PER LAYER	24
UNIT PER PALLET	96

LBS PER PALLET	1,725
----------------	-------

COLORS	Reflectance	Stock
Almond Grove	SR. n/a sRI n/a	✓
Granite	SR. n/a sRI n/a	✓
Sierra	SR. n/a sRI n/a	✓



ALMOND GROVE



LIMESTONE



SIERRA

The following accessories are available for any fire pit kit.
 Contact your local Territory Manager for details.



ROUND FIRE SCREEN
 (works with Sunset Round only)



24" SWING AWAY GRILL



KETTLE HOOK



ACCESSORY POST WITH COLLAR

Single Unit



ROMANSTACK ROUND W/INSERT
 1525 x 1525 x 400mm
 60 x 60 x 15 3/4"

FIRE PIT WARNING

Wood-burning fire pits must be lined with a proper metal insert or refractory (fire-rated) brick to protect the concrete components from extreme exposure to heat. Extreme heat on a concrete surface may affect the structural integrity of the concrete and can be dangerous. The floor of the fire pit should always be constructed using refractory brick or a sand bed. For your safety, always use a spark screen over the fire.

Notes: All measurements are nominal. Contact Unilock for more information.

Natural Stone Cleaners



UNICARE NATURAL STONE ACID CLEAN

1L and 5L

Removal of:

- Cement Staining
- Efflorescence
- Iron Oxide (Rust) Cement mortar
- Grout



UNICARE NATURAL POWER CLEAN

1L and 5L

Removal of:

- Oil & Grease
- Food Stains
- General Dirt & Mud
- Sap & certain plant stains
- Light cement contamination (on acid-sensitive surfaces)



UNICARE BIOCLEAN

1L and 5L

Removal of:

- Black spot algae
- Green algae
- Plant stains from leaves, wood, trees, berries & flowers
- Organic staining from bark & compost
- Colored stains from food spills, tea, coffee and wine

Natural Stone Sealers



UNICARE NATURAL STONE NAT MATTE SEALER

1L and 5L

For Porous Stones

- No change of color
- No surface coating, sheen or shine at all
- Riven Sandstone & Smooth Sandstone



UNICARE NATURAL STONE NATCOLOR ENHANCE SEALER

1L and 5L

Color Enhancement For Porous Stones

- No surface coating, sheen or shine
- Breathable
- Lasts several years
- Easy to apply

Cleaners



TECHNISEAL® PROFESSIONAL GRADE OIL/ GREASE REMOVER

1 Quart

An industrial strength petroleum-based product remover that lifts and absorbs embedded oil and grease stains as it dries from a liquid to a powder. Specially formulated for concrete pavers, slabs and walls, natural stone, poured or stamped concrete, etc. It works without damaging or discoloring the material and is easy to use.

Cleaners continued



TECHNISEAL® EFFLORESCENCE REMOVER

1 Gallon Box of 4 x 1 US Gallon

Specially formulated to dissolve efflorescence (whitish salt deposit) and remove ground-in dirt on paving stones and concrete, without discoloring or damaging surfaces. It cleans evenly, and enables the sealant to better penetrate the material to be treated.



TECHNISEAL ORGANIC STAIN REMOVER

700g Box of 6 x 700g 500 Units per skid

Formulated to remove moss and mildew as well as tough organic stains such as dead leaves, blood, wine and non-greasy food stains on concrete pavers, slabs and walls, natural stone, etc; requires minimum scrubbing.



TECHNISEAL SR SLURRY REMOVER FOR PAVERS AND SLABS

1 Gallon Box of 4 x 1 US Gallon

This is the most effective product available for removing cement slurry and polymeric sand haze on concrete or clay pavers and slabs. One gallon of concentrated product cleans up to 600 sq. ft. Coverage will depend on surface condition and product dilution.

ALLIANCE CLEANERS AND SEALERS AVAILABLE

Sealers



SUREBOND 1300 JOINT SAND STABILIZING SEALER - MATTE FINISH

1 and 5 Gallon 55 Gallon drum (Special Order)
(4 - 1 Gal/case, 36 cases/skid)(36 - 5 Gal/skid)

- **Dual-Purpose Product:** Seals surface & hardens joint sand
- **Antifungal Film Protection:** Protects sealer film from mold, moss & algae
- **Stabilizes Joint Sand:** Reduces sand washout, weeds & insect infestation
- **Clean Fresh Look:** Locks in a clean, natural look & matte finish
- **Breathable, Immediate Application Water-Based Sealer:** Does not trap moisture or efflorescence
Approximate Coverage: 80-120 sq. ft



SUREBOND 7700 JOINT STABILIZING SEALER - GLOSS FINISH W/ANTIFUNGAL PROTECTION

1 and 5 Gallon 55 Gallon drum (Special Order)
(4 - 1 Gal/case, 36 cases/skid)(36 - 5 Gal/skid)

- **Multi-Purpose Product:** Seals & moderately enhances surface and hardens joint sand
- **Antifungal Film Protection:** Protects sealer film from mold, moss & algae
- **Stain Resistant:** Promotes easier cleaning & maintenance
- **Stabilizes Joint Sand:** Reduces sand washout, weeds & insect infestation
- **Surface Enhancement:** Moderately enhances surface tone & semi-gloss finish
- **Breathable, Immediate Application Sealer:** Does not trap moisture or efflorescence
Approximate Coverage: 80-120 sq. ft

Sealers continued

SUREBOND 8700 WET LOOK JOINT STABILIZING SEALER WITH ANTIFUNGAL PROTECTION

1 and 5 Gallon 55 Gallon drum (Special Order)
(4 - 1 Gal/case, 36 cases/skid)(36 - 5 Gal/skid)



- **Multi-Purpose Product:** Seals & enhances surface, hardens joint sand
 - **Antifungal Film Protection:** Protects sealer film from mold, moss & algae
 - **Stain Resistant:** Promotes easier cleaning & maintenance
 - **Stabilizes Joint Sand:** Reduces sand washout, weeds & insect infestation
 - **Surface Enhancement:** Deeply enhances surface tone & semi-gloss finish
 - **Rain Safe in 90 Minutes:** Minimizes rain affecting your sealing schedule
 - **Breathable, Immediate Application:** does not trap moisture or efflorescence
- Approximate Coverage: 80-120 sq.ft

Adhesives continued



ALLIANCE XP GATOR BLOCK ADHESIVE

RS-ADH039 10 oz; 12/case; 90 cases/skid (1080 ea)
RS-ADH040 28 oz; 12/case; 60 cases/skid (720 ea)

- Bonds permanently in 24 hours
- Material may be repositioned for up to 30 minutes
- Works in temperatures above 32°F
- 850 psi in 24 hrs (1000 psi in 7 days)

Sands

POLYBIND G2 SAND

NO DUST • HAZE FREE • NO BLOWER • ONE WATERING • RAIN SAFE IN 16 MINUTES

Designed for paver joints up to 2".

- A unique mix of polymer binders and calibrated sand
 - Installation almost identical to regular paver joint sand, except for the application of water. Becomes very firm when set & locks between the paver joints.
- Colors:** Oxford Grey and Nevada Tan
Packaging: 50 lb bag / 56 bags per skid
Coverage: 65-85 sq.ft./ bag for narrow joints, larger joints will require more sand



Adhesives

TECHNISEAL STICKY STONE

10 oz. Caulk Tube: 20' at 1/4" Bead (Case of 12)
28 oz. Caulk Tube: 50' at 1/4" Bead (Case of 12)

Professional-grade vertical hardscape adhesive bonds various construction substrates beautifully and durably.

Surface Type: Natural Stone, Concrete Paver, Porcelain Tile, Wood

Coverage: Coverage power will depend on the dimensions of the application surface. eg. 5mmx5mm deep area, a single 600ml sausage will cover 50 linear feet. On an 8mmx6mm deep area, the same size will cover 40 linear feet.



TECHNISEAL® HP NEXTGEL POLYMERIC SAND

NO DUST • NO HAZE • NO WASTE

Designed for paver joints up to a maximum of 1 inch.

- Ideal in high-humidity environments, heavy-vehicular traffic areas & steeper terrain
- Fast, clean, durable and profitable installation thanks to Nextgel technology.
- Offers great resistance to weed growth, insect invasion and erosion; fast-setting within minutes of water activation.

Colors: Urban Grey, Granite Grey and Tan

Packaging: 50 lb bag / 56 bags per skid

Coverage: 65-85 sq.ft. coverage per bag for narrow joints, larger joints will require more sand



TECHNISEAL STRUCTURE BOND (& GUN)

24 oz. Container: (Case of 12 / 84 boxes per pallet)

Super-strength hardscape foam adhesive, specifically for the construction industry. Quick & easy precise application with the special "Gun II" dispenser; adjustable bead size. 3/8" bead size will yield up to 600ft.

Clean Up: Cured foam can only be removed mechanically. Use Structure Bond Gun Cleaner to clean gun upright. Product does not have a flash point after it dries. See cleaner below.

TECHNISEAL PROSERIES SMARTSAND POLYMERIC SAND

Designed for paver joints up to a maximum of 1 inch.

- Benefits from the Nextgel technology for cleaner application and faster wetting
- A smart choice for residential driveways, patios, etc.
- Offers great resistance to weed growth, insect invasion and erosion; fast-setting within minutes of water activation.

Colors: Urban Grey, Granite Grey and Tan

Packaging: 50 lb bag / 56 bags/skid (2860lbs/skid)

Coverage: 65-85 sq.ft. coverage per bag for narrow joints, larger joints will require more sand installation. Recommended **with extra care** for use with Copthorne®, Courtstone®, Richcliff®, Town Hall® & Umbriano® products. It is **not suitable** for use with Il Campo®, Series™ and Unigranite®. Umbriano's surface must be cleaned with a foam squeegee post installation.



TECHNISEAL STRUCTURE BOND™ GUN CLEANER

24 oz. Container: (Case of 12 / 84 boxes per pallet)

Structure Bond Gun Cleaner is a powerful cleansing formula that rapidly dissolves any uncured Structure Bond adhesive residue. It is specifically designed to fit Structure Bond Gun II dispensers. Simply screw a canister onto the gun and press the trigger to cleanse the tool from uncured product. The built-in sprayer nozzle will also dissolve any spill, drip or adhesive residue.



Note: Carefully read all instructions and safety information on product label prior to application. For additional safety information, see MSDS.

Sands continued



POLYBIND G2 COMPLETE SAND

NO DUST • HAZE FREE • NO BLOWER • ONE WATERING • RAIN SAFE IN 16 MINUTES

Designed for paver joints up to 2".

- Made with calibrated sand mixed with sophisticated intelligent polymers, which neutralizes haze and dust.
- Recommended for a variety of uses including pool decks, patios, footpaths, driveways, parking spaces, pavements, etc.

Colors: Nevada Tan & Oxford Grey

Packaging: 50 lb/bag Coverage: 65-85 sq.ft./bag for narrow joints / larger joints will require more sand

ROMEX EASY ECOFINE SAND **NEW**

Sustainable Paving Joint Mortar for Narrow Joints

- Designed for paver joints up to 1/8" (porcelain) to 2" (concrete pavers)
- Made from 98% natural, recycled or renewable raw materials

- Resin film free • weed resistant • ant resistant
- Highly water permeable • frost resistant
- Installation almost identical to regular paver joint sand, except for the application of water. Becomes very firm when set & locks between the paver joints.

Colors: Neutral, Stone Grey & Basalt

Packaging: 27.5 lb bucket / ? per skid

Coverage: ?-? sq.ft./ bag for narrow joints, larger joints will require more sand



GATOR AQUA ROCK

- Manufactured to meet ASTM No.9 requirements for permeable paver joint units; calibrated for the majority of permeable pavers
- High strength granite stone for long-term use
- Helps prevent erosion
- Reduction of stormwater runoff

Color: Granite Grey

Packaging: 50 lb bag / 56 bags per skid

Coverage: 20-25 sq.ft. per bag for a 60mm paver

PERMA PAVER EDGING


- Designed to float and flex with the sub base and not work independently like standard edging and spikes
- Quick & easy to install, typically cutting edging install time down by 90%
- Stays under the soil/mulch grade - invisible edging
- Combats the freeze/thaw cycles in cold weather; won't deteriorate in moist/humid conditions
- Coverage per container: yields approximately 25-30 lineal feet of edging per bucket




Edge Restraints

SNAPEDGE ONE-PIECE EDGING THAT DOES IT ALL!

- Only one part required for straight runs or curved installations
- Built-in connector fastens one piece to the next - convenient 96" size, makes them easy to transport
- Unique 'Snip and Flex' feature speeds installation of curves and corners without pre-planning
- The open design allows a root system to grow through SnapEdge, further reinforcing the installation
- Engineered to provide a strong, easy-to-install edge restraint for concrete/clay pavers
- Nail hole bosses are full-length cylinders. Hammer blows will not fracture or force nail heads through edging



Typical Cross Section



1. SnapEdge
2. 10" Spiral Spike
3. Soil
4. Turf
5. Sand Jointed Paver
6. Sand Jetting Course
7. Aggregate Base
8. Compacted Subgrade

SNAPEDGE LOW PROFILE EDGE RESTRAINT

- Built-in connection fastens one piece to the next
- Unique 'Snip and Flex' feature speeds installation of curves and corners without pre-planning
- One piece can be used for straight or curved installations
- Spike bosses every 4" on center. Recommended spike spacing is 1 spike every foot for driveways and 1 spike every 16" for patios and walkways.
- Open base design promotes root system development and growth right through the base further strengthening the installation

Snip 'n Flex
One Piece System



Integral Connection



1 3/8"
Side
Wall



1 7/8"
Side
Wall



Low Profile

SnapEdge

Paver Spacers


X & T SLAB SPACERS

- Unilock recommends using slab spacers when installing Arcana on an open grade surface.

• "T" spacers are needed for running bond patterns; "X" spacers are needed for stack bond patterns. Please contact your sales manager for more information.

Packaging:

- 250 per bag
- X & T bagged separately
- X spacers 2" x 2" (RS-ACC237)
- T spacers 2" x 1" (RS-ACC236)



RS-EDGE061



- 1 piece = 8 linear feet
- 1 bundle = 24 pieces
- 1 bundle = 24 pieces = 192 linear feet
- 1 pallet = 16 bundles = 3,072 linear feet

Note: Carefully read all instructions and safety information on product label prior to application. For additional safety information, see MSDS.

PaverSaver Uni Mat



PAVERSAVER UNI MAT

Universal Design - for use on most compactors

The PaverSaver Uni Mat is made out of a specially formulated urethane rubber. Material soft enough to protect the paver surface yet hard enough to minimally affect travel speed. The universal sizing fits most compactor plates and easily attaches and detaches from the compactor.

UniLyft™



- Install up to 700 sq. ft. per hour!
- Access tight or narrow areas
- Eliminate the need for a forklift on site
- Reduce labor costs
- Reduce shoulder, hand and knee pain and injury
- Improve your bottom line
- Financing available

Contact your local rep for details



Landscape Fabric & Grid System



GEOGRID AND FABRICS

Strata 150 - 22.22 sq. yds/roll

Strata 200 - 200 sq. yds/roll

Filter Fabric - 6.25' x 360'; 250 sq yds/roll




LANDSCAPE SPIKES

50lb case

UNILOCK DRIVEGRID™ SYSTEM

- 120' x 13' Roll, 1,572 Square Feet/Roll, 56 lb/Roll



WHY DRIVEGRID SYSTEM™?

- ✓ Easy to install
- ✓ Reduces overall project cost
- ✓ Inexpensive
- ✓ Proven Tensar® TriAx® Technology



Grid Systems and Landscape Fabric continued



GATOR GRID 30-30

- A biaxial geogrid, provides strength, longevity, excellent stress transfer and prevents failure to the internal structure of landing areas, retaining walls and steep slopes
- Has a high molecular weight as well as high-tenacity polyester yards which are woven in tension and finished with a PVC coating.
- Packaging & Unilock SKU (Minimum Case Purchase = MCP):
 FAB070 - 4' x 50/12 rolls/case, 60 rolls/skid *MCP*
 FAB071 **SPECIAL ORDER** - 6' x 50' - 40 rolls/skid
 FAB072 - 6' x 150'/25 rolls/skid



GATOR FABRIC NON-WOVEN 4.4

- A needle punched non-woven geotextile made of polypropylene fiber, ideal for drainage, filtration and will allow water flow of 135 gallons per minutes per square foot (613 L/min/sq. m.) in paver or retaining wall applications
- Its filament fibers are used for soil separation and drainage and combine high durability along with excellent physical and hydraulic properties. I
- Non-biodegradable and resistant to most soil chemicals
- Packaging & Unilock SKU (Minimum Case Purchase = MCP):
 FAB043 - 3' x 100' - 6 rolls/case, 24 rolls/skid **SPECIAL ORDER** *MCP*
 FAB044 - 4' x 100' - 6 rolls/case, 36 rolls/skid *MCP*
 FAB046 - 6' x 100' - 30 rolls/skid *MCP*
 FAB047 - 6' x 300' - 16 rolls/skid *MCP*

Base/Drainage Systems

GATOR TILE SYSTEM

Contact Unilock for more information.



RS-ACC074-1



RS-ACC087



10oz - RS-ADH039
28oz - RS-ADH040



RS-ACC088



Beige - RS-SAND136
Black - RS-SAND139
Grey - RS-SAND137
Ivory - RS-SAND138

Visit alliancegator.com/gator-base/ for more details and videos

PRODUCT SPECIFICATIONS



DRIVECEL30 LIGHT DUTY
20 x 20 x 1.2"
500 x 500 x 30mm



DRIVECEL50 HEAVY DUTY
20 x 20 x 2"
500 x 500 x 50mm

TECHNICAL INFORMATION

Conforms to:

- DIN 38412 - Neutral for the environment, lifespan higher than 10 years
- DIN 4102 - Approval emergency access routes, fire resistance
- DIN 1072 - Approval for 20 tonne axle load, driveways, road extensions, bridges
- DIN IN ISO 124 and B125 - Approval for car parks, access roads & storage areas

Maximum Load Capacity = 1,000 tonnes / m² (filled)

Temperature Range = -35°C to 85°C (-31°F to 185 °F)

Tile Wall Thickness = 3 mm (for GF50, GF40 & GF30)

Performance Design Life = >100 years

ENVIRONMENTAL INFORMATION

- Made from 100% recycled plastic
- Recyclable
- Neutral for the environment

PRODUCT DATA

Tiles & Bundling	Unit	Area Per (m ² / ft ²)		Units Per		Per Bundle		Mass Per (kg / lbs)	
	Thickness	Unit	Bundle	Layer	Bundle	Layers	Dimensions	Unit	Bundle
DriveCel30 Light Duty	1.2" (30mm)	0.250 / 2.69	80 / 861.1	4 (2x2)	320	80	1.05 x 1.05 x 2.55 m 3.44 x 3.44 x 8.37 ft	1.1 / 2.4	352 / 776.0
DriveCel50 Heavy Duty	2" (50mm)	0.250 / 2.69	48 / 516.7	4 (2x2)	192	48	1.05 x 1.05 x 2.55 m 3.44 x 3.44 x 8.37 ft	1.6 / 3.5	307.2 / 677.2

Notes: Engineering services are available for site-specific designs and drawings. For more information or for custom options, please contact your Unilock Territory Manager or call 1-800-UNILOCK.


Base Thickness Chart (General)

APPLICATION	GRAVEL BASE	BEDDING COURSE	BACKFILL WIDTH (WALLS ONLY)
PATIOS, WALKWAYS, POOL DECKS	4" - 6" (10cm-15cm)	1" (2.5cm)	
DRIVEWAYS	8" - 12" (20cm - 30cm)	1" (2.5cm)	
STEPS, PLANTERS, RAISED PATIO	6" (15cm)	0 - 1/8" (0cm - 0.3cm)	8" - 12" (20cm - 30cm)
RETAINING WALLS UNDER 18" (45cm)	6" (15cm)	0 - 1/8" (0cm - 0.3cm)	12" (30cm)
RETAINING WALLS OVER 18" (45cm)	6" (15cm)	0 - 1/8" (0cm - 0.3cm)	16" (50cm)

Soil condition - In areas with poor soil conditions, (eg., heavy clay, disturbed soils) increase the depth of the base to provide more stability. Where poor soil conditions exist it may be advisable to contact an engineer when constructing a retaining wall in excess of 24" in height.

Area = (Length) x (Width)	Metric Equivalents
Area of a Circle = 3.14 x (Radius) x (Radius)	1 inch = 2.5400 centimeters 1 centimeter = 0.3937 inch
Area of a Half Circle = 1.57 x (Radius) x (Radius)	1 foot = 0.3048 meter 1 meter = 39.3701 inches
Area of a Quarter Circle = .78 x (Radius) x (Radius)	1 yard = 0.9144 meter
Area of a Triangle = (1/2 Base) x (Height)	1 sq. foot = 929.030 sq.centimeters
Perimeter of a Circle = 6.28 x (Radius)	1 sq. meter = 1.196 sq. yards
Perimeter of a Half Circle = 3.14 x (Radius)	27 cu feet = 1 cu. yard
Perimeter of a Quarter Circle = 1.57 x (Radius)	

Typical Paver Cross Section



Aspect Ratio

Simply defined, the aspect ratio is the overall length of a paver divided by its height.

$$\text{LENGTH/HEIGHT} = \text{ASPECT RATIO}$$

If an insufficient aspect ratio is used, any flexing or rocking caused by movement on the surface such as pedestrian or vehicular traffic, could result in breakage of the paver units. Not only is this breakage unsightly, but it can also compromise the integrity of the segmental system.

3 : 1 or less
Heavy-Duty Vehicular

4 : 1
Light-Duty Vehicular

Over 5 : 1
Pedestrian

BEDDING MATERIALS CHART (APPROXIMATE IMPERIAL TONS)

Bedding Course												
Square Feet	1"	2"	3"	4"	5"	6"	7"	8"	9"	10"	11"	12"
50	0.3	0.5	0.8	1.0	1.3	1.5	1.8	2.0	2.3	2.5	2.8	3.0
100	0.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0
150	0.8	1.5	2.3	3.0	3.8	4.5	5.3	6.0	6.8	7.5	8.3	9.0
200	1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0
250	1.3	2.5	3.8	5.0	6.3	7.5	8.8	10.0	11.36	12.5	13.8	15.0
300	1.5	3.0	4.5	6.0	7.5	9.0	10.5	12.0	13.5	15.0	16.5	18.0
350	1.8	3.5	5.3	7.0	8.8	10.5	12.3	14.0	15.8	17.5	19.3	21.0
400	2.0	4.0	6.0	8.0	10.0	12.0	14.0	16.0	18.0	20.2	22.0	24.0
450	2.3	4.5	6.8	9.8	11.3	13.5	15.8	18.0	20.3	22.5	24.8	27.0
500	2.5	5.0	7.5	10.0	12.5	15.0	17.5	20.0	22.5	25.0	27.5	30.0
550	2.8	5.5	8.3	11.0	13.8	16.5	19.3	22.0	24.8	27.5	30.3	33.0
600	3.0	6.0	9.0	12.0	15.0	18.0	21.0	24.0	27.0	30.0	33.0	36.0
650	3.3	6.5	9.8	13.0	16.3	19.5	22.8	26.0	29.3	32.5	35.8	39.0
700	3.5	7.0	10.5	14.0	17.5	21.0	24.5	28.0	31.5	35.0	38.5	42.0
750	3.8	7.5	11.36	15.0	18.8	22.5	26.3	30.0	33.8	37.5	41.3	45.0
800	4.0	8.0	12.0	16.0	20.0	24.0	28.0	32.0	36.0	40.0	44.0	48.0
850	4.3	8.5	12.8	17.0	21.3	25.5	29.8	34.0	38.3	42.5	46.8	51.0
900	4.5	9.0	13.5	18.0	22.5	27.0	31.5	36.0	40.5	45.0	49.5	54.0
950	4.8	9.5	14.3	19.0	23.8	28.5	33.3	38.0	42.8	47.5	52.3	57.0
1000	5.0	10.0	15.0	20.0	25.0	30.0	35.0	40.0	45.0	50.0	55.0	60.0

BASE DEPTH CHARTS (CUBIC YARDS)

Bedding Course												
Square Feet	1"	2"	3"	4"	5"	6"	7"	8"	9"	10"	11"	12"
50	0.2	0.3	0.5	0.6	0.8	0.9	1.1	1.2	1.4	1.5	1.7	1.9
100	0.3	0.6	0.9	1.2	1.5	1.9	2.2	2.5	2.8	3.1	3.4	3.7
150	0.5	0.9	1.4	1.9	2.3	2.8	3.2	3.7	4.2	4.6	5.1	5.6
200	0.6	1.2	1.9	2.5	3.1	3.7	4.3	4.9	5.6	6.2	6.8	7.4
250	0.8	1.5	2.3	3.1	3.9	4.6	5.4	6.2	6.9	7.7	8.5	9.3
300	0.9	1.9	2.8	3.7	4.6	5.6	6.5	7.4	8.3	9.3	10.2	11.1
350	1.1	2.2	3.2	4.3	5.4	6.5	7.6	8.6	9.7	10.8	11.9	13.0
400	1.2	2.5	3.7	4.9	6.2	7.4	8.6	9.9	11.1	12.3	13.6	14.8
450	1.4	2.8	4.2	5.6	6.9	8.3	9.7	11.1	12.5	13.9	15.3	16.7
500	1.5	3.1	4.6	6.2	7.7	9.3	10.8	12.3	13.9	15.4	17.0	18.5
550	1.7	3.4	5.1	6.8	8.5	10.2	11.9	13.6	15.3	17.0	18.7	20.4
600	1.9	3.7	5.6	7.4	9.3	11.1	13.0	14.8	16.7	18.5	20.4	22.2
650	2.0	4.0	6.0	8.0	10.0	12.0	14.0	16.0	18.1	20.1	22.1	24.1
700	2.2	4.3	6.5	8.6	10.8	13.0	15.1	17.3	19.4	21.6	23.8	25.9
750	2.3	4.6	6.9	9.3	11.6	13.9	16.2	18.5	20.8	23.1	25.5	27.8
800	2.5	4.9	7.4	9.9	12.3	14.8	17.3	19.8	22.2	24.7	27.2	29.6
850	2.6	5.2	7.9	10.5	13.1	15.7	18.4	21.0	23.6	26.2	28.9	31.5
900	2.8	5.6	8.3	11.1	13.9	16.7	19.4	22.2	25.0	27.8	30.6	33.3
950	2.9	5.9	8.8	11.7	14.7	17.6	20.5	23.5	26.4	29.3	32.3	35.2
1000	3.1	6.2	9.3	12.3	15.4	18.5	21.6	24.7	27.8	30.9	34.0	37.0

Actual volume may vary due to type of materials, moisture content, and compaction. Calculation charts and formulas are provided as a service by Unilock for estimating material requirements. Unilock will not be held responsible in any way for resulting product overage or shortage.

IMPORTANT NOTES

UNILOCK PAVER PATTERNS

This Product Data Guide contains an extensive reference to patterns and designs. The purpose of these pattern swatches is to help the designer plan unique and exceptional designs. The percentages of products shown are based on the pattern and not on bundle configurations. In fact, there may be situations in which a pattern has been created with one particular size of stone, but that stone only comes packaged with two other sizes. This means that the designer will have to plan how the other components are used in the overall plan. This is usually accomplished by adding a border or an accent. As a result, overages or shortages may occur in certain patterns. The designer and/or installer of Unilock products accepts all responsibility for design and all associated costs incurred as a result of applying any of Unilock's suggested design patterns in a project. Please plan your project and review your order carefully prior to ordering.

PRODUCT HANDLING WARNING

Bundle Straps Under Tension - Use extreme caution when removing or handling straps. Always wear gloves, goggles, safety footwear, and protective clothing when removing or handling straps. Failure to do so may result in serious bodily injury or loss of sight.

Cut all concrete products only in well ventilated areas. Inhalation of dust is a serious health risk. A "NIOSH" (US) or a "CSA" (CDN) approved respirator, safety goggles, hearing protectors, and gloves must be worn at all times. Always "wet-cut" or "wet grind" concrete products to minimize dust.

Do not stack bundled concrete products higher than 2 bundles high. Contents of the bundle may be unstable and subject to topple when stacked. Always use extreme caution and appropriate equipment when transporting or storing bundled concrete products. Failure to do so may result in serious bodily injury or death. Always obey gross vehicle weight (GVW) loading limitations and regulations.

Hazard Rating: Fire 0, Health 1, Reactivity 0. See MSDS Concrete Masonry (Pavers). Contact Unilock for complete sheet or view safety information at Unilock.com.

Unilock assumes no liability or responsibility for loss or damage, resulting from the improper use or handling of our products, or from failure to follow instructions, warnings, and/or advisories on the product label, and on the MSDS sheet.

TRADEMARK & LEGAL INFORMATION

Unilock Ltd. and Hengestone Holdings, Inc. are the owners or authorized users of all trademarks used in this publication unless otherwise specified. Umbriano® are trademarks of Metten Stein + Design GmbH & Co KG used under license by Unilock®. Measurements throughout this portfolio are nominal. Not all products shown are available at all Unilock locations. Log on to Unilock.com for availability. Colors shown in this catalog should be used only as a guide. Colors should always be chosen from actual samples. Contact your local Unilock representative for color availability in your area.

©2023 Hengestone Holdings, Inc.



QUALITY COMMITMENT

Unilock was the first concrete paver manufacturer in North America to offer a Lifetime Guarantee, and since then we have continued to stand behind it to ensure customers are completely satisfied with our products. With almost 2 billion stones in the ground, that's quite the commitment!

Our products are better and stronger than other brands. In fact, our internal standards of manufacturing in the USA and Canada far exceed industry standards set by ASTM (American Society for Testing and Materials) and CSA (Canadian Standards Association) and other European organizations.



LIFETIME GUARANTEE - RESIDENTIAL

Our Transferable Lifetime Guarantee warranties the structural integrity of Unilock concrete paving stones and retaining wall units when used in residential applications. It covers any structural failure or deterioration of the concrete unit resulting from normal use or from the reasonable application of sodium chloride (common rock salt used for de-icing). StoneMark™ products have the same warranties as Unilock paving stones and retaining walls, but cannot be warranted against damage resulting from de-icing products.

Any materials installed and maintained to our guidelines, and subject to normal wear, that prove defective, will be replaced without cost. Proof of purchase is required. Customers are encouraged to submit receipts to us as soon as their project is complete, using the Unilock Warranty Registration Form on our website (Unilock.com).

Purchasers need to ensure that the product they purchase is appropriate for their intended application; for example, only certain thicknesses of products are appropriate for driveways. Color matching of the replacement product and/or lost time cannot be guaranteed and labor costs related to installing replacement product is not included. Unilock reserves the right to seek a professional diagnosis and opinion to determine the exact cause of the product failure. If the failure falls within our warranty parameters, Unilock will replace the defective product.

EXCLUSIONS - Unfortunately, some things are beyond the control of Unilock, and are therefore not covered by this warranty. These include: naturally occurring efflorescence, hazing from polymeric jointing sand, scratching and chipping resulting from snow removal or construction equipment, damage caused by natural or un-natural disasters, or negligence by anyone other than Unilock. While EasyClean helps to increase a paver's resistance to staining from various substances, it does not make our products stain-proof nor does it resist every kind of stain. The Unilock warranty also does not cover deterioration or damage as a result of poor design or poor installation practices that are contrary to specifications as laid out by ICPI (Interlocking Concrete Pavement

Institute) and the NCMA (National Concrete Masonry Association). For more information please visit www.icpi.org and www.ncma.org. Additionally, please refer to the Maintenance, Color and Installation Advisories.

MAINTENANCE ADVISORY

1. Cleaning and Sealing

As with anything that is outdoors, Unilock products are subject to harsh weather, dust, acid rain, leaf stains, water stains and general wear from foot or vehicular traffic. Therefore, periodic cleaning using environmentally safe detergents designed for cleaning concrete is recommended to maintain a bright, fresh appearance.

To make subsequent cleaning easier and more effective, a concrete sealer can be applied to new or cleaned products to help prevent the penetration of substances that can cause stains.

There are many types of concrete cleaners and sealers on the market. Always read the instructions carefully before using the product to make sure that it will function as expected. Testing first, in a small unobtrusive area, is always a good idea to ensure the results are acceptable. Consult your local hardscape dealer to find the products best suited for your paver or wall installation.

2. Winter Maintenance

Snow removal by way of metal blades on plows or shovels will scratch and chip the surface of pavers, causing permanent damage. To mitigate this risk, metal snow clearing blades must always have a polyurethane or rubber cutting edge attached when plowing pavers. De-icing Salts - The use of de-icing products on

Visit Unilock.com to register for your Transferable Lifetime Guarantee.



paver surfaces is important for safety and to help mitigate snow accumulation. Most de-icing products will have some effect on concrete, even if the product label indicates that it is safe on concrete. If you must use a de-icing product, we recommend that you use Sodium Chloride (ordinary rock salt) or Calcium Chloride (for colder climates). Always apply sparingly. The use of de-icing products on StoneMark, wet-cast pavers, slabs or coping may damage the product and therefore is not recommended. Whenever possible use a coarse sand as an anti-slip measure instead of de-icing chemicals.

COLOR ADVISORY

1. Selection

Due to the inherently variable nature of printed materials and digital monitors, Unilock cannot guarantee that products will match the color of printed or online images. Therefore, when making final product selections, decisions should be made based on actual stones which are readily available from Unilock, Authorized Contractors or Authorized Dealers. Most Unilock products are not comprised of a single color, but rather contain blended colors for a more natural appearance. This means that there will be significant color variance from stone to stone, so purchasers should view multiple units together to get a more accurate impression of the overall color. *Note:* Unilock Natural Stone variations are outside the control of Unilock. Purchasers of natural stone must be willing to accept this inherent variability.

2. Pre-installation checking

Always check the label to ensure that the Unilock product delivered to your project is the product and color ordered.

If there is a discrepancy, or if the product inside the packaging doesn't appear to be correct, contact your hardscape dealer before installing any pavers or wall units. If the product is installed, it indicates your acceptance of the products as delivered.

3. Blending

If the project requires more than one bundle of product it's always a good idea to draw product from several bundles when installing, as this ensures that any variation between bundles will be seamlessly integrated in the project. When bundles are from different production runs, random selection from multiple bundles is even more important.

4. Efflorescence

Efflorescence is a naturally occurring process that may appear as a white or light grey powder on the surface of concrete, clay or natural stone. It is temporary, and will disappear over time. However, if it is bothersome, an efflorescence cleaner can be used to remove it. There is no way to predict or prevent efflorescence. Because it does not compromise the structural integrity of the product, it is not covered by Unilock product warranties.

INSTALLATION ADVISORY

1. Construction Residue

While a certain amount of dirt on pavers and walls is inevitable during the construction phase, installers are strongly encouraged to clean as they go as construction residue can embed in the surface and become difficult to remove. The slurry produced during wet-saw cutting is particularly stubborn to clean if allowed to dry on the surface of pavers. Unilock warranties do not cover

stains caused by a failure to remove construction residue.

2. Polymeric Haze

Surface hazing caused by polymeric jointing sand is not the responsibility of Unilock. Polymeric jointing sand should only be installed by an experienced and knowledgeable contractor.

Any sand that is left on the surface prior to activation will result in a haze that is very difficult and time-consuming to remove. Only the highest quality, brand name polymeric sand that is guaranteed by the manufacturer should be used.

3. Compaction Damage

Both smooth and textured paver surfaces can be scratched by compaction equipment used to 'flatten' a new paver installation. Therefore, metal plate compactors must be fitted with a polyethylene mat to protect the paver surface from becoming scratched, or a superior option is to use a rubber-roller compactor instead. Damage to product surfaces caused by failure to follow these instructions is not covered by Unilock product warranties.

FIRE PIT WARNING

Wood-burning fire pits must be lined with a proper metal insert or refractory (fire-rated) brick to protect the concrete components from extreme exposure to heat. Extreme heat on a concrete surface may affect the structural integrity of the concrete and can be dangerous. The floor of the fire pit should always be constructed using refractory brick or a sand bed. For your safety, always use a spark screen over the fire.

BOSTON PRODUCT DIRECTORY

UNIT PAVERS

Product	Page	Finish	Pedestrian	Residential Vehicular	Commercial Vehicular	Environmental	For Borders & Accents
ADA Paver Premier	04	S	✓	✓	✓		
Arcana™	05	S	✓				
Artline™ Smooth	06	SM/S	✓	✓			
Artline™ Umbriano	07	SM	✓	✓			
Beacon Hill™ Flagstone	08	F	✓	80mm			
Beacon Hill™ Smooth	10	SM	✓	80mm			
Bristol Valley®	11	S	✓				
Brussels Brock®	12	W	✓	✓			✓
Camelot®	13	S	✓	✓	✓		✓
Cophthorne®	14	T	✓	✓			✓
Courtstone®	15	C	✓	✓			✓
Dura-Mat™	16	S			✓	✓	
Eco-Line®	17	CU	✓	✓	✓	✓	
Eco-Optiloc™	18	S	✓	✓	✓	✓	
Eco-Priora™	19	B	✓	✓	✓	✓	
Eco-Promenade™	20	S	✓	✓	✓	✓	
Eco-Stone™	21	CU	✓	✓	✓	✓	✓
Granito™	22	S	✓	✓			
Hex Paver	23	S	✓	✓	80mm		
Hollandstone™	24	S	✓	✓	✓		✓
Holland Premier®	25	S	✓	✓	✓		✓
Il Campo®	26	B	✓	✓	✓		✓
Mattoni™	27	T	✓	✓			✓
Natural Stone	28	SM	✓				
Nordic Cobble™	33	WS	✓	✓	✓		✓
Optiloc™	34	S	✓	✓	✓		
Porcelain	35	SM	✓				
Promenade® Paver	36	CU	✓	✓	✓		✓
Revela®	37	S	✓				
Richcliff®	38	F	✓	✓			✓
Series™	39	WS	✓	✓	✓		✓
Thornbury™ Smooth	40	SM	✓	✓	✓	✓	
Town Hall®	41	T	✓	✓	✓	✓	✓
Transition™	42	F	✓	✓			
Treo® Premier	43	F	✓	✓			
Treo Smooth	44	S	✓	✓	✓	✓	
Tribeca Cobble	45	W/C	✓	✓		✓	✓
Turfstone™	46	S		✓	✓	✓	
Umbriano®	47	SZ	✓	70mm	80mm		✓
Westport™	49	F	✓	✓			✓

RETAINING WALLS

Product	Page	Finish	Gardens	Retaining Walls	Steps	Seatwalls	Pillars
Brussels Dimensional System™	50	W	✓	✓	✓	✓	✓
Concord Wall™	51	SP	✓	✓	✓		
DuraHold®	52	S		✓			
DuraHold2®	54	S		✓			
Estate Wall™	55	SP/W	✓		✓	✓	✓
Fullnose Edger™	73	SZ			✓		
Lineo™ Dimensional Stone	60	SZ	✓		✓	✓	✓
SienaStone®	62	SP		✓	✓		
SienaEdge®	63	F		✓	✓		
U-Cara®	64	Various	✓	✓		✓	✓

Finishes: B=Brushed; C=Cobblestone; CU=Custom; D=Dimpled; DW=Dimpled and Weathered; F=Flagstone; S=Standard; SM=Smooth; SZ=Smooth Zero Bevel; SP=Split; SP/W=Split and Weathered; T=Timeworn; W=Weathered; WS=Washed

This application chart should only be used as a guide. Site conditions, base materials, pattern and frequency of use may vary the performance of various types and styles of products.

J-CARA®

THE MOST COMPLETE HARDSCAPE WALL SYSTEM





Let's **BUILD YOUR BUSINESS** together.

**CONTACT 1-800-UNILOCK OR VISIT UNILOCK.COM TO
CONNECT WITH YOUR LOCAL TERRITORY MANAGER**

BOSTON
(508) 278-4536

CHICAGO
(630) 892-9191

MILWAUKEE
(262) 742-3890

KANSAS
(913) 417-7985

MICHIGAN
(248) 437-7037

NEW YORK
(845) 278-6700

MID-ATLANTIC
(202) 798-2060

ONTARIO
(416) 646-9000

CINCINNATI/KY/TN
(513) 202-0219

**OHIO/WESTERN PA/
WNY&CNY**
(330) 927-4000

UNILOCK.COM | 1-800-UNILOCK

©2023 Hengestone Holdings, Inc.